SUNVEY & ONUMENTABIAN COUNTY REMONIMENTATION

	MAR 2 6	? 100¢						•				
	MINU & C	3 1330	LAND CORN	ER RECORDAT	TION CERTIFI	ICATE	į.					
or com	ers in GOMM	ISSION	Filing Requi	rement of Act 7	74, Mich. P.A.	1970	50 >>	A.	F			
	(County)	Loca	ated In:	Corner C	ode#		100	5103	22	. : <u>2</u>		
. Publ	ic Land Survey	•	13 N. 6 E. T R T R			,	NTY MICHIG	THE OF DEED!	12 35 PH.	NECURUEU	ייייייייייייייייייייייייייייייייייייי	
	erty Controlling	s	T R T R	•				กกิจ	S. S.	ກວ		
	ection elianeous	s	T R T R	-			15.	UUO) :	40	•	
	erty in Section	\$	T R			Register	of Deed	ls Stair	np & File	Numb	er	
·	•							:		:		
							ВС	D E	F.G ·H	- J	к	L
. Priva	ite Claims									<u>].</u>]	·	Γ
						3		Ĭ				
Pone	ald C. Prevost		1 1	2	05	4	_}_	8	: .			 12~
Kona	ald C. Fievosi	, in a field sur	July 1 vev on	3	95 . 19	5	1 .	<u> </u>	ĬĬĬ	<u>-1 </u>		Ĺ
Inlines 1 and 2 above were in conformance with regulations and rules therefore as required in the current nanual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and is above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:								20	28 27	23-		24-
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.						12 13	-31	32	1 33 34 1	-35- 		36-
A. Des	cription of origin	al monument a	and accessories	and/or subseque	ent restoration:		٠.			: : .	•	
A-1	40.00 Set 1/2 I Sugar 8" I Sugar 12"	Mile Post, 50.0 N.76°W. 1 S.14 1/2° E. 1 led as M-1, T.	09 Lynn, 75.46 S 14 L 20 L	c 31, T.14 NR.(et Post Corner of	on Towns 13 &	: 14 North, F	. •	& 6 E	ist		•	
3. Des	scription of come	er evidence fou	und and/or meth	od applied in rest	toring or reesta	blishing com	er:	. •			• •	
A-1	Found 3/8" Ro Distance West See Agreeable	od in Small M 2617.15 (261 Witnesses Be	on. Box 17.73 R) elow	idence of the po	-	-	5, s ²	•			•	
			:	1			Ed land c	ORNER			•	

County Representative

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

	5 1 10/00 5 1 tot #/ou st au			
A-1	Replaced 3/8" Rod with 5/8" X 24'	' Re-Bar with 2 3/4" Bay Co	. Brass Cap in existing Mon. Box on	7:13-95
			a man dale in amorning with most our	

Nail & Ribbon E. Face P. Pole P.K. Nail W. Face P. Pole

S.40°W. 56.71 (57.1 to U.P. LCRC L2 P506)

1/2" Re-Rod

N.45°W. 41.17 (41.25 to P.K. LCRC L2 P506)

Cross on E. Conc. Headwall

Surveyor's Michigan License No.

N.40°E. 56.61

S.30°E. 30.84

Cross on W. Conc. Headwall

S.45°W. 34.95

24612

JRVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983 FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS.

BONALD C

PAEVOSŤ

ROFESSIONAL SURVEYOR