

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

BENZIE

(County)

Located in:

Corner Code #

1. Public Land Survey

T 27N R 13W

C-6

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, CARL KIISKILA, in a field survey on OCTOBER 2, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-6

6.I.L.O. SET POST - 12" SUGAR MAPLE S40°W 17.2' AND 12" SUGAR MAPLE N51°E 9.9'. HAROLD R. BRUNING, 1974 L.C.R.C. SET BENZIE CO. MONUMENT ON PREVIOUS SURVEY. DNR SURVEY CREW FOUND BENZIE CO. MONUMENT FITTING HAROLD R. BRUNING 1974 L.C.R.C. AND WITNESSES.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-6

FOUND BENZIE CO. MONUMENT PER HAROLD R. BRUNING, 1974 L.C.R.C. AND WITNESSES.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-6

FD BENZIE CO CAST IRON MON AND SET CARSONITE POST.
11°S.MAPLE N14°W 31.07' (DROVE SPIKE W/BCRP TAG E. SIDE)
119° ASH N16°E 22.98' (DROVE SPIKE W/BCRP TAG SE SIDE)
8°TW.S.MAPLE EAST 4.42' (DROVE SPIKE W/BCRP TAG S SIDE)
17°S.MAPLE S35°E 12.08' (DROVE SPIKE W/BCRP TAG NE SIDE) CTR OF BIT RD (IN CURVE NW & S) IS WEST 50' +/- 2'.

1 = PS H.BRUNING 1974 WIT.



Signed by Carl T. Kiiskila
Surveyor's Michigan License No. 33981

Date 4-9-97