

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

BENZIE

(County)

Located In:

Corner Code #

1. Public Land Survey

T22N R 13W

A-8

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous

S

T R

Property In Sec.

S

T R

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, CARL KIISKILA, in a field survey of JULY 1, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		10		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

A-8

G.L.O. SET POST - 15" BEECH N54°W 4.6' AND 20" BEECH S52°E
23.8'. NO EVIDENCE OF THIS G.L.O. POST OR BEARING TREES WAS
FOUND.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-8

REESTABLISHED CORNER BY SINGLE PROPORTIONATE MEASUREMENT
BETWEEN FOUND SECTION CORNER TO THE NORTH AND REESTABLISHED
CORNER TO THE SOUTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-8

SET 4"x 36" CONC MON W/BENZIE CO REMON PROGRAM BRASS CAP AND CARSONITE POST.

21" S. MAPLE (CLP 4) N60°W 12.43'

4" BEECH N52°E 16.52'

19" S. MAPLE (CLP) S25°W 19.08'

6" BEECH (CLP) N86°E 27.60'



Signed by Carl T. Kiiskila

Date 4-9-97

Surveyor's Michigan License No. 33981