

SURVEY &  
REMONUMENTATION

APR 14 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 2 PAGE 71

For corners in

BENZIE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 27N R 13W

C-8

2. Property Controlling  
in Section

S

T

R

3. Miscellaneous  
Property in Sec.

S

T

R

S

T

R

STATE OF MICHIGAN  
BENZIE COUNTY  
RECORDED

15 Jan 1998 4:08:04 PM  
MICHELLE R. GRAY  
REGISTER OF DEEDS  
# PAGES One

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, CARL KIISKILA, in a field survey on OCTOBER 2, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-8

G.L.O. SET POST - 6" SUGAR MAPLE S42°W 19.1' AND 6" BEECH N68°E 15.8'. WM. BATZER, 1975 L.C.R.C. IN LIBER 1, PAGE 118 FOUND 5" X 2' HIGH POST AND REPLACED IT WITH 1" X 30" PIPE.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-8

FOUND 3/4" GALV. PIPE FITTING WM. BATZER L.C.R.C. AND WITNESSES.

Ratified by Peer Group  
In accordance with P.A. 345

Chairman [Signature]

Date 7/24/1996

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-8

SET 4"x 36" CONC MON W/BENZIE CO REMON PROGRAM BRASS CAP IN PLACE OF FD 3/4"x 30" IRON PIPE AND SET CARSONITE POST.

#10°R.PINE N25°W 21.06' (DROVE SPIKE W/BCRP TAG NE SIDE)

#10°S.MAPLE(CLP) N45°E 34.89' (DROVE SPIKE W/BCRP TAG SE SIDE)

#13°R.PINE N60°E 64.55' (DROVE SPIKE W/BCRP TAG NW SIDE)

#9°R.PINE S65°E 55.18' (DROVE SPIKE W/BCRP TAG NE SIDE)

#19°B.CHERRY S05°E 2.38' (DROVE SPIKE W/BCRP TAG E SIDE)

N-S WINDING TRAIL IS 150' +/- WEST. E-W WINDING TRAIL IS 65' +/- S.

\*= PS, WM.BATZER 1975 WIT.

\*= WIT BY OTHERS.

Signed by Carl T. Kiiskila

Surveyor's Michigan License No. 33981

Date 4-9-97

