

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

BENZIE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 27N R 14W

T R

T R

T R

2. Property Controlling
In Section

S 27

T R

S 21

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, CARL T. KIISKILA, in a field survey on JULY 9, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1

7

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1

7

ESTABLISHED THE NE COR OF NW1/4 OF NW1/4 S-27 PER STANDARD BLM INSTRUCTIONS.

ESTABLISHED NE COR OF SE1/4 OF NE1/4 OF S-21 PER STANDARD BLM INSTRUCTIONS. CORNER IS IN LINE W/OLD B/WIRE FN REMAINS (IN TREES) W'LY & 31' EAST OF OLD N-S B/WIRE FN REMAINS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1

7

SET 5/8" REROD W/PS CAP & CARSONITE POST.

4" W.ASH N15°W 20.82'

18" B.CHERRY N10°E 18.32'

4" W.ASH N85°E 24.20'

4" S.MAPLE S55°E 19.99'

CTR OF TRAIL (NW-SE) WEST 59'

SET 5/8" x 3/4" REROD W/PS CAP.

28" BEECH N65°W 35.10'

10" R.PINE N60°E 57.72'

POWER POLE S80°E 28.78'

6" TW.S.MAPLE S70°W 32.43'

SET CARSONITE POST W/LOC TAG WEST 33'

Signed by Carl T. Kiiskila

Date 4-9-97

Surveyor's Michigan License No. 33981