RATIFIED BY THE BERRIEN COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN RECORDED BERRIEN COUNTY REMONUMENTATION 345 OF 1990 LAND CORNER RECORDATION CERTIFICATE DEC 13 10 50 AM 195 Filing Requirement of Act 74, Mich. P.A. 1970 Burner Levelnery Located In: Corner Code ## REGISTER DE DET DS CAR T 8 S R 18 W 1. Public Land Survey T _____ R ____ _ R : **Property Controlling** in Section S Ţ 3. Miscellaneous s Т Register of Deeds Stamp & File Number Property in Sec. _, Recorded Plat 5. Private Claims _ 3 1, Robert W. Prestine, in a field survey on November 24, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as 10 expressed below: NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. 12 A. Description of original monument and accessories and/or subsequent restoration: 12/13/95 111#2978 A66 C-9 Southeast Corner of Section 19, T. 8 S., R. 18 W. \$7.00 Govt. 111#2978 AAA 12/13/95 Raised mound in Prairie STATE REMON FEE \$2.00 No wits. B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Did not find corner. Set in line with W.P.A. monuments . ENGRICION on State Line as set for Indiana State Line in Section 8, T. 38 N., R. 1 E. (1938) with occupation to North. MAR 2 7 1996 COMMISSION C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: OF MICHIG Set 4" round Berrien County Remonumentation monument Nail & tag in 13" W. Cherry N 16° W 28.25' Nail & tag in 14" W. Cherry N 65° W 25.18'
Nail & tag in 9" W. Cherry S 85° W 10.84' PRESTINE Angle iron fence cor. post in conc. North 1.10' LAND SURVEYOR This position is accepted as a careful and faithful No reestablishment of the position of the original corner.

LIBER 3PAGE 323

Signed by Robert W. Prestine

Surveyor's Michigan License No. ___18662_

SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983

ED LAND

December 11,

CHARRENERS BELLEVILLE

1995