

SURVEY &  
REMONUMENTATION

FEB 08 1999

SECTION

BRANCH COUNTY REMONUMATION PROGRAM  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

BRANCH COUNTY  
BUTLER TWP

Located In:

Corner Code #

1. Public Land Survey

T.5 S. R.5 W.

C-9

T. R.

T. R.

T. R.

2. Property Controlling  
in Section

S. T. R.

S.

T. R.

3. Miscellaneous

S.

T. R.

Property in Sec.

S.

T. R.

STATE OF MICHIGAN  
Branch County  
Recorded

11-04-1998 15:46:15

Linda Lee Morrison-Mathews  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

ACCEPTED BY THE BRANCH COUNTY  
SURVEY PEER GROUP AS THE OFFICIAL  
CORNER UNDER MICHIGAN PUBLIC ACT 345  
OF 1990 AT MEETING HELD ON

9-09-1998

E.R. Reed Co. Rep.

E.R. REED

4. Lot No. , Recorded Plat

5. Private Claims

I, EDWARD W. REED, in a field survey on JUNE 6, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 19-20-29-30

A. Description of original monument and accessories and/or subsequent restoration:

1825: R. CLARK, JR, D.S. - CORNER SET

1856: M. KNOWLES. D.S. - STONE

1972: E.R. REED, CO SURVEYOR - FOUND STONE WITH PIECES OF BRICK, SET 5/8" X 18" REBAR IRON  
RECORDED IN LCRC # II-0012

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 5/8" X 18 IRON OVER STONE AS DESCRIBED IN LCRC # II-0012

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1/2" X 18" REBAR IRON ROD WITH REMON CAP IN CI-MONUMENT BOX FLUSH WITH PAVED ROAD SURFACE OVER STONE

TEL PED	N 60 W	56.1' TO CENTER
CONC. ANCHOR POST	N 50 E	46.4' TO CENTER
36" MAPLE	N 33 E	57.8' TO CENTER
POWER POLE	S 65 E	107.8' TO FACE
28" MAPLE	N 54 W	53.5' TO CENTER
24" MAPLE	N 11 W	92.0 TO CENTER

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION  
OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

*Edward W. Reed*

EDWARD W, REED

Date

9-9-98

Surveyor's Michigan License No. 33985

Liber 000003 Page 0212

