

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

APPROVED
Date Oct 18 1995
CALHOUN COUNTY
REMONUMENTATION.

For corners in
Calhoun
(County) Located In: Corner Code #

1. Public Land Survey	T	4	S	R	7	W.	J-11
	T			R			
	T			R			
	T			R			
2. Property Controlling in Section	S		T		R		
	S		T		R		
3. Miscellaneous Property in Section	S		T		R		
	S		T		R		

STATE OF MICHIGAN
CALHOUN COUNTY
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Michael A. Groat, in a field survey on October 16, 19 95,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found
as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1826 Lyon
30" Elm N 14° E 28 Links
7" B. Ash S 86° W 13½ Links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Traversed between the Southeast and Southwest corners of Section 26
and set corner mid way on line. The corner falls in the gravel road
in a cut area so no evidence of the original corner was found.

CORNER
REMONUMENTATION

FEB 22 1996

COMMISSION

LIBER 1828 PAGE 35

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Harrison monument from which:

Nail and spotter in 20" Beech, N 35° W, 39.05'
Nail and spotter in 6" Ash, N 44° E, 22.0'
Nail and spotter in 10" Hickory, S 47° E, 35.5'
Nail and spotter in 12" Hickory, S 31° W, 31.3'



Signed by Michael A. Groat
Surveyor's Michigan License No. 39079

Date 10-16-95