

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

CHIPPEWA CO.

4 CORNERS

FOR CORNERS OF—	LOCATED IN—	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. <u> </u> N. <u> </u> E. <u> </u> S. <u> </u> R. <u> </u> W. <u> </u>	
2. PROPERTY CONTROLLING IN SECTION <u>10</u>	T. <u>41</u> N. <u>XX</u> E. <u>XX</u> S. <u>XX</u> R. <u>6</u> W. <u>XX</u>	<u>5, 9, 6, 4</u>
3. MISCELLANEOUS PROPERTY IN SECTION	T. <u> </u> N. <u> </u> E. <u> </u> S. <u> </u> R. <u> </u> W. <u> </u>	
4. LOT NO. <u> </u> , RECORDED PLAT <u> </u>		
5. PRIVATE CLAIMS <u> </u>		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Gerald L. Wiggins, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 5-24, 1988, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- 5 North 1/16 Corner of Section 10. Not previously set.
- 9 East 1/16 Corner of Section 10. Not previously set.
- 6 N.E. 1/16 Corner of Section 10. Not previously set.
- 4 N.W. 1/16 Corner of Section 10. Not previously set.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 5 Corner set M.P.O.L. between the computed Center Corner and the North 1/4 Corner of Section 10. Corner lies West of Road 36.5'.
- 9 Corner set M.P.O.L. between the computed Center Corner and the East 1/4 Corner of Section 10.
- 6 Corner set at the Center of the N.E. 1/4 of Section 10 by closed traverse.
- 4 Corner set at the Center of the N.W. 1/4 of Section 10 by closed traverse.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- DNR Monument set at all 4 corners.
- 5 10" Cedar, N45°E, 16.2' & 8" Twin Cedar, N85°W, 13.5' & 8" Cedar, S40°W, 32.0' & 6" Cedar, S79°E, 29.45'
- 9 6" Maple, N60°W, 16.85' & 8" Maple, N28°W, 14.1' & 8" Maple, N30°E, 27.3' & 6" Maple, S2°W, 22.45'.
- 6 16" Aspen, S86°W, 14.1' & 6" Balsam, S20°W, 17.0' & 12" W. Birch, S36°E, 48.3' & Tag in Power Pole, N27°W, 21.1'.
- 4 20" W. Pine, N78°E, 10.8' & 16" W. Pine, N11°W, 44.2' & 20" W. Pine, N57°W, 48.6' & 26" W. Pine, S59°W, 55.1'.

SIGNED BY Gerald L. Wiggins

DATE 6-30-88

SURVEYOR'S MICHIGAN REGISTRATION NO. 23521


FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY DATE

MICHIGAN REGISTERED LAND SURVEYOR



(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET