

APR 1 1999

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Corner #7.00 LAND CORNER

For corners in

SECTION

Chippewa County

Located in:

Corner Code #

1. Public Land Survey

T44N R2W

E-11

2. Property Controlling  
in Section

S  
S

T  
T

R  
R

3. Miscellaneous  
Property in Sec.

S  
S

T  
T

R  
R

4. Lot No. , Recorded Plat

5. Private Claims

\$2.00 MSSR

5 MAR 1999 2:01:36 PM Receipt #14029

RECEIVED FOR RECORD

CHIPPewa COUNTY - STATE OF MICHIGAN  
SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 11 PAGE 15

Register of Deeds Stamp & File Number

I, Keith R. Waters, in a field survey on November 20, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-11 Corner Common to Sections 28, 29, 32, & 33, T44N, R2W

1845 - Original corner established by James Mullett.

Witnesses: Aspen 12, S59°E 11 links - Aspen 12, S48°W 11 links.

1905 - Chippewa County Surveyor Frederick H. Brown, RLS 944, notes indicate an original corner here, being the only original corner in this vicinity. A large cedar post and monument.

Circa 1930's - Chippewa County Surveyor corner tie book shows this corner with several witnesses.

1991 - LCRC, liber 7, page 333, Chippewa County corner records. Keith R. Waters, P.S. 33142, found 3/4" iron bar.

Witnesses: 6" x 6" Concrete USGS Monument, S62°E 50.35'

Power Pole (PD4/151/43), S52°W 34.12'

12" Scotch Pine, N72°W 70.80'

Twin 8" Aspen, N38°E 63.60'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.  
Found a 3/4" iron bar and all record witness objects as called for in the above mentioned 1991 LCRC.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found a 3/4" iron bar at the corner location, which falls in the intersection of Centerline Road and 23 Mile Road.  
Witnesses:

6" x 6" Concrete USGS Monument with Brass Tablet (stamped "TT 64 S 1929"), S62°E 50.35'

Nail and witness tag in side of Power Pole (PD4/151/43), S52°W 34.12'

Nail and witness tag in side of 12" Scotch Pine, N72°W 70.80'

Nail and witness tag in side of Twin 8" Aspen, N38°E 63.60'



Signed by Keith R. Waters

Date 12-30-98

Surveyor's Michigan License No. 33142

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995

BOOK 11 PAGE 15