

MAR 09 1994

CHIPPEWA COUNTY REMONUMENTATION CORNER

RECEIVED FOR RECORD  
CHIPPEWA COUNTY  
STATE OF MICHIGAN

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC 30 PM 2:44

*J. Roger Matthe*  
REGISTER OF DEEDS

For corners in  
Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey

T 45N R 1E

B-7

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. Recorded Plat

5. Private Claims

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Keith R. Waters

November 23

93

I hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-7 1/4 Corner Common to Sections 18 & 19, T45N, R1E

Original ties to post: Maple 10, N23°W 21 links  
Ironwood 8, S44°E 22 links



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-7 (T45N, R1E)

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a 1/2" iron pin with plastic cap #29251 (Larry R. Rogers) 0.4 feet north of centerline of east-west asphalt road (15 Mile Road) at a fence line to the north. Distance to Section corner east is 2617.92 feet and distance to Section corner west is 2378.62 feet, which appears to be a proration of the overall mile as shown in County Surveyor notes. Corner is 37.6 feet south of a straight line between said Section corners. Considerable bend at 1/4 corner is also consistent with County Surveyor notes. Accepted corner as found and established witness objects.

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-7 (T45N, R1E)

Corner is a 1/2" iron pin with cap #29251 0.4 feet north of centerline of 15 Mile Road at a fence line to the north. Witnesses:

Corner Fence Post, S29°E 47.10'  
9" Spruce, N08°W 51.10' (Not blazed)  
5" White Birch, N19°E 39.98'  
8" Spruce, S05°E 65.01'

Note: Distances are to a nail and tag #29251 in the side of witness object. Except as noted, trees are blazed and painted. Bearings are compass bearings corrected for declination.

igned by *Keith R. Waters*

Date 12-30-93

veyor's Michigan License No. 33142