

# FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Chippewa Co.

3 Corners.

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>45</u> N. <u>X</u> R. <u>1</u> E. <u>X</u>	<u>L-10</u>
2. PROPERTY CONTROLLING IN SECTION <u>25</u>	T. <u>45</u> N. <u>X</u> R. <u>1</u> E. <u>X</u>	<u>11, 12</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ R. _____ E. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, David B. Babbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 7-11, 1984, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- L-10 Center Corner of Section 25. Not prev. set.
- 11 S.W. 1/16 Corner of Section 25. Not prev. set.
- 12 South 1/16 Corner of Section 25. Not prev. set.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- L-10 Corner set at intersection of N-S and E-W 1/4 lines of Section 25 by closed traverse.
- 11 Set at center of the S.W. 1/4 of Section 25 by closed traverse.
- 12 Set M.P.O.L. between Center Corner and South 1/4 Corner of Section 25.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D.N.R. Monument set at all three corners. Bearings:

- L-10 14" Y. Birch, N67°W, 33.2' & 16" Spruce, N80°E, 24.95' & 6" H. Maple, S79°E, 53.4' & 6" H. Maple, S68°E, 71.0'.
- 11 8" H. Maple, N75°E, 98.3' & 12" H. Maple, S86°E, 82.9' & 8" H. Maple, S63°E, 94.6' & 8" B. Ash, S50°E, 47.6'.
- 12 9" Aspen, N24°W, 3.4' & 6" H. Maple, N6°W, 29.6' & 14" Twin R. Maple, S53°E, 20.8' & 5" H. Maple, S57°W, 12.7'.

SIGNED BY

*David B. Babbitt*  
David B. Babbitt

DATE 9-17-84

SURVEYOR'S MICHIGAN REGISTRATION NO. 21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES: