

## CHIPPEWA COUNTY REMONUMENTATION CORNER

RECEIVED FOR RECORD  
CHIPPEWA COUNTY  
STATE OF MICHIGAN

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC -3 PM 3: 56

For corners in  
Chippewa  
(County)

Located In:

Corner Code ##

1. Public Land Survey

T47N R 1E

A-1/A-2/Same

T47N R 1W

M-1/M-2/Corner

T R

T R

2. Property Controlling

S T R

In Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

*J. Roger Malott*  
REGISTER OF DEEDSSURVEY &  
REMONUMENTATION

JUL 22 1999

Register of Deeds Stamp &amp; File Number

SECTION

I, Keith R. Waters in a field survey on September 24, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-1/A-2 (T47N, R1E)

Witness Corner to Meander Corner Section 6, T47N, R1E &amp; Section 1, T47N, R1W. (Northern Terminus of the Michigan Meridian)

Original ties to post:

(Wm. A. Burt, D.S., 1840)

Spruce 8, S40½°E 2.30 chains

Spruce 7, S64°E 2.51 links

Corner is recorded in liber 1, page 192, in 1976 by James H. Granger, P.S. 16041, as a rectangular concrete monument with brass tablet on top with the following witnesses:

Witness Plaque in R.R. Abutment, WEST 5.1'

Power Pole, S63°E 18.6'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-1/A-2 (T47N, R1E)

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a concrete monument (48"x48" at base and 18"x18" at top, approximately 4 feet high), with a brass Chippewa County tablet on top as called for in previous recording. Monument also has a plaque on the side which indicates that it was set by the Upper Peninsula Chapter of the Michigan Society of Registered Land Surveyors. Corner is on the east side of a railroad bridge, approximately 30 north of the centerline of Portage Avenue, and is approximately 100 feet west of the centerline of the International Bridge overhead. Accepted corner as found and established new witness objects:

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-1/A-2 (T47N, R1E)

Corner is a 4 foot high concrete monument with brass tablet as described above. Witnesses:

Power Pole (A19-1), S58°E 18.98'

Power Pole (A19-4), S85°E 124.12'

Brass Witness Tablet in the East

Face of R.R. Abutment, S78°W 5.24'

Brass Tablet in West Face of

International Bridge Abutment

(NGS BM V295, 1983), S27°E 91.91'

Note: Bearings are compass bearings corrected for declination (may be somewhat erratic due to all the iron in the area). Distances to poles are to a nail and tag in the side. Distances are measured with EDM.

Signed by Keith R. WatersDate 11-30-93Surveyor's Michigan License No. 33142FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN. 1, 1983

L-8 pg 42 Other code: 3

