

CHIPPEWA COUNTY REMONUMENTATION CORNER

RECEIVED FOR RECORD
CHIPPEWA COUNTY
STATE OF MICHIGANSURVEY &
REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC -3 PM 3: 57

For corners in
Chippewa

JUL 22 1999

Located in:

Corner Code #

(County)

1. Public Land Survey SECTION T 47N R 1E F-7/G-7 #5
T R
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

Keith R. Waters

September 17 93

I, Keith R. Waters, in a field survey on September 17, 19 93
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F-7/G-7 Corner Between Sections 16 & 21, at the Intersection of the
Southeasterly Line of the Methodist Mission Reserve, T47N, R1E.

Original ties to post:
Hemlock 20, N15°E 08 links
Hemlock 8, S05°W 09 links

This corner is shown on a survey by William L.
Karr, P.S. 27450, of Northwoods Land Surveying,
Inc., dated October 28, 1987, as a 1/2" cap #27450.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-7/G-7 (T47N, R1E)

This corner is being perpetuated as part of the Chippewa County
Remonumentation Program.

Found a 1/2" iron pin with cap #27450 approximately 9 feet north of the
centerline of east-west asphalt road (3 Mile Road), and approximately 60 west
of the centerline of a gravel road to the south (Lincoln Avenue) as shown on
Northwoods survey. Accepted corner as found and established four witness
objects.

Note: An iron recorded in liber 6, page 315, Chippewa County corner records,
as the 1/4 corner between Sections 16 & 21 was found 608.81 feet west
of this corner. There was no 1/4 corner established in the original
Public Land Survey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-7/G-7 (T47N, R1E)

Corner is a 1/2" iron pin with cap #27450 approximately 9 feet north of the
centerline of 3 Mile Road, approximately 60 west of Lincoln Avenue.

Witnesses:

7" Red Maple, N25°W 48.56'
9" Spruce, N59°E 51.54'
Power Pole, S61°E 101.20'
Power Pole (DR3-210), S34°W 49.00'

Note: Distances are to a nail and tag
in the side of witness object.
Bearings are compass bearings
corrected for declination. Trees are
blazed and painted. Distances
measured with EDM.

igned by Keith R. Waters
urveyor's Michigan License No. 33142

Date 11-30-93

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

L. 8 pg. 48

Other code: 5

