

## CHIPPEWA COUNTY REMONUMENTATION CORNER

RECEIVED FOR RECORD  
CHIPPEWA COUNTY  
STATE OF MICHIGANSURVEY & REMONUMENTATION AND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC -3 PM 3:57

For corners in  
Chippewa

(County)

JUL 22 1999

Located In:

Corner Code #

J. Roger Malott  
REGISTER OF DEEDS

1. Public Land Survey SECTION 47N R 1E  
T R  
T R  
T R
2. Property Controlling in Section S T R  
S T R
3. Miscellaneous S T R  
Property in Sec. S T R

H-7/I-7 #6

Register of Deeds Stamp &amp; File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Keith R. Waters, in a field survey on November 29, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:

H-7/I-7 (T47N, R1E)

Witness Corner to Meander Corner Sections 15 &amp; 22, T47N, R1E.

Original corner was 5.50 chains (363 feet) east of 1/4 corner common to Sections 15 & 22. Original witnesses:

Black Ash 10, N87°W 1.60 chains  
Birch 12, S48°W 1.27 chains

The line between Sections 15 & 22 is shown on Assessors Subdivision No. 12.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-7/I-7 (T47N, R1E)

This corner is being re-established as part of the Chippewa County Remonumentation Program.

Found no evidence of corner or its accessories. Re-established corner on the easterly extension of the south line of Lot 535 of Assessors Subdivision No. 12, as established in previous surveys. Corner is 128.80 feet from a found iron at the southwest corner of said Lot 535, and is approximately 10 feet from the shore of the Saint Marys River.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-7/I-7 (T47N, R1E).

Corner is a 3/4" x 24" rebar with 3/4" aluminum Chippewa County Remonumentation cap approximately 10 feet from the shore of the Saint Marys River. Witnesses:

Triple 4" Red Maple, S87°W 77.79'  
6" White Birch, N58°W 58.71'  
7" Ash, S41°E 42.13'  
7" Ash, S19°W 70.26'

Note: Distances are to a nail and tag in the side of witness object. Bearings are compass bearings corrected for declination. Distances measured with EDM. Trees are not blazed.

Signed by Keith R. WatersDate 11-30-93Surveyor's Michigan License No. 33142

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

L. 8 pg 45 Other code: 6

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

