

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey

T 49N R 7W

F3

T R

T R

S T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Oct 04 2005

I, Stephan J. Szyszkoski, in a field survey on \_\_\_\_\_, 20\_\_\_\_ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(F3) Quarter corner common to Sections 4 and 9. 1849 - Established by Wells Burt, Deputy Surveyor: "West corrected between Sections 4 and 9 ...40.02 Set Fir post qr. section corner. Spruce 6 S65E 32 links, W.Pine 8 N74W 7 links. ...80.04 Section corner". Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(F3) The original post and accessories were not recovered. Found no evidence of the position of the original corner on the ground. Reestablished the corner by single proportionate measurement to the original record and on the section line between corner E3 2652.95' West and corner G3 2652.95' East.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(F3) Set 1"IDx36" I.pipe with 4" alum.

MDNR cap. Set measuring nails in:

14" J.Pine S08W 27.44' mrd "1/4S NBT"

16" R.Pine S32E 39.3' do

15" W.Pine S51E 45.04' do

6" Maple N45E 49.55' do

Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski

Date 2/21/06

Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Office of Land and Facilities