

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED
E 110-95
95 OCT -3 PM 2:50

For corners in
CLARE
(County)

Located In:

Corner Code #

REGISTER OF DEEDS
CLARE COUNTY
DONNA M. CARR

1. Public Land Survey T 19N R 5W J-7
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Section S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, MARK R. ROBISON, in a field survey on SEPTEMBER, 19 95,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found
as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-7: 1/4 Corner common to Sections 14 & 23

1856 ADAIR, SHUGAR 9 N16W 22, SHUGAR 8 S39E 15

MDOT 3/4" PIPE DUE NORTH 32.62' FENCE CORNER
DUE SOUTH 58.96' POWER POLE
S55W 75.63' 20" MAPLE

10-72 LAPHAM, NO COR. MATERIAL L.C.R.C.
(SAME AS ABOVE)

SURVEY &
REMONUMENTATION
DEC 6 1995
COMMISSION

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1	12	11	10	9	8	7
3	7	6	5	4	3	2	13	12	11	10	9	8
4	8	7	6	5	4	3	14	13	12	11	10	9
5	9	8	7	6	5	4	15	14	13	12	11	10
6	10	9	8	7	6	5	16	15	14	13	12	11
7	11	10	9	8	7	6	17	16	15	14	13	12
8	12	11	10	9	8	7	18	17	16	15	14	13
9	13	12	11	10	9	8	19	18	17	16	15	14
10	14	13	12	11	10	9	20	19	18	17	16	15
11	15	14	13	12	11	10	21	20	19	18	17	16
12	16	15	14	13	12	11	22	21	20	19	18	17
13	17	16	15	14	13	12	23	22	21	20	19	18

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4"x15" PIPE IN CENTER-LINE OF OLD M-61 (ABANDONED) FOUND MDOT WITNESSES. MEAS.
WEST 2634.17 FEET (MDOT 2634.36') TO I-7 AND EAST 2624.75 FEET TO K-7

APPROVED LAND CORNER
P.A. 345 of 1990
Clare County

Chairman Mark R. Robison
Date 9-26-95

This Corner established in Clare County Remonumentation Program.

See dossier for detailed report.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-7: 1/4 Corner common to Sections 14 & 23
SET 5/8"x36" RE-ROD WITH 3" CLARE COUNTY REMON CAP MARKED 1995 P.S. NO. 27458
ACCEPTED AS BEST AVAILABLE EVIDENCE OF THE ACCEPTED POSITION OF THE CORNER.

WITNESSES:
DUE NORTH 32.62' - NAIL & TAG IN FENCE POST (OBT)
DUE SOUTH 58.96' - NAIL & TAG IN POWER POLE (OBT)
S70°W 40.75' - N/W CORNER OF SMALL BARN (16'x20')
N39°30'W 63.70' - NAIL & TAG IN APPLE TREE



Signed by Mark R. Robison

Date 10-03-95

Surveyor's Michigan License No. 27458

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1973
REVISED JAN., 1983