LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970
Clare County Remonumentation

								0	
For Corners In: Clare (County)	Located In			Corner C	ode#				
1. Public Land Survey			ON R 3W	A3					
Property Controlling in Section	s	T	ON R 4W R R	M3					
Miscellaneous Property in Section	s s	· ' — · T —	R R				Daniston of Door	ode Otener S F	W
4. Lot No:	Recorde	d Plat:			 -		Register of Dee	eus Stamp & F	ile Number
5. Private Claims:			•	~		1 A B	CDEF	G H I	KLM
I, Craig W. McVean, in a frequirements of PA 74, Mid and 2 above were in conforthe current manual of sur Interior, Bureau of Land Macorner points mentioned in of the Michigan Board of established, re-established,	chigan PA o mance with vey instruct anagement o lines 3, 4 au f Land Sun	of 1970, to regulations of to by a defended to the contract of	the corner point ons and rules the United Statecree of a Couve were in control by a Decre	ats mentioned in therefore as re- ates Department of Law and/or formance with the of a Court	n lines 1 quired in nt of the that the the rules of Law:	3 4 7 5 18 19 9		10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	112
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.									5-36-
- CSR – L. 3, p	ost – H. Ni N66°W 5 I 34°W 38 L. - G. E. Ada I47°E 42 L. 65°E 39 L. p. 15 – A. I 8 ½°E 39; I p. 56 – W. Maple N30 evidence for c. Corner or rd survey.	cholson L. ir – 185 D. Johns Birch 8" S. Moor SE 53.7 ound an ommon No evid	- 1839 6 son - 1909 N71°W 56 ½ e - 1956 '; PP S70°E d/or method to Sec. 6 & 7 lence of ½" pel road is 4.5	117.0' applied in resi ', T20N, R3W ipe but based	- Rec Sur LCRC - # S45°E 46 N30°W 39 - Rec. Sur. Same wit Rec. Sur. w/ cap #1 Maple clu S50°W sp Bell Riser toring or re-early son found will	- L. 2, p. 14 272-77 - P. .60' - PP; S. 3.35' - 2" Ma - L. 3, p. 43 as Lapham - L. 3, p. 78 8223 - 5' S. mp - 39.12'; b. in Cor. Fer 45.58'. establishing of	B. Lapham – 45°W 65.70' aple 88 – P. D. Ca	1977 – Fd. – 8" Apple; se – 1994 – harty – 1996 Road.; N22°\ n 12" Maple '; S50°E top	Fd. ½" pipe – 6 – Set 5/8" rerod N Sp. in E. side Clp. 54.42'; C.L.
C. Description of monum									
A3 & M3 - Replaced 5/8 around cap - Down 0.6 N21°W 39.11' to set N N20°E 54.46' to set N 8 S19°E 96.32' to set N 8 S45°W 50.42' to fd. Pk -DNR Mon. used and a	& T in E. s & T in W. s & T in W. s in NW side	ide 6" R ide 13" ide 11" l e RR tie	R. Maple Clp. R. Maple (HL R. Pine corner post of Clare Co. I	7 (HLF, PBL) .F) (HLF)		n 1" x 36" G	alv. Iron pipe	To The LICENSED	CRAIG W. McVEAN PROFESSIONAL SURVEYOR No. 39088
Signed by: Surveyor's Michigan L	icerse No		Me 1/2 39088		Date:	8/27	/2003	To Bear	OFESSIONAL