## SURVEY & REMONUMENTATION

MAR 2 1 1997

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

JIBER	4,	PAGE	154

For come@MMISSION	Ė										
Clinton (County)	Located III.	Corner Code #		Ju	7 . 3	8 1	1 AH	'96			
Public Land Survey	T R T R T R R T R R R R R R R R R R R R	T R T R		REGISTALL DE CEEDS CLINION COLORS MANGELY							
Property Controlling S 3     in Section S 3     Miscellaneous S Property in Sec. S 5	36 T 7N R 1W T R T R T R	1.4	Register of Deeds Stamp & File Number								
4. Lot No, Record	ded Plat			В	C D	E F	в н	JK	LM		
5. Private Claims			2	6	5	Å	3	2	1		
I. Norman C. Caldwell in a field survey on April 1996.  do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded				7	8	Ŷ	10	11	12		
				18	17	16	15	14	13		
				19	20	21	22	23	24		
				30	29	28	27	26	25		
on this certificate.		11   12	31	32	33	34	35	36			
·	e SE 1/4 of Section 36	and/or subsequent restoration:	13 1	I,,	J	. <b>.</b>	1				

This position not established by the original government survey.

Clinton County Surveyor record, book #5 at page 24, indicates a stone monument was placed by Charles E. Hollister, Clinton County Surveyor, date not recited, but about 21 April 1902, at the midpoint between the Township Corner and Standard East 1/4 Corner of Section 36

There are no additional record references to this position.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

The Hollister 6" x 8" x 12" stone was found at the intersection of an ancient fence North, South and West during a complete and extensive retracement of the Michigan Meridian in performance of a contract with the Clinton and Shiawassee County Remonumentation efforts. This monument was utilized as evidence for the placement of the Township Corner of T6 & 7N, RIW, Victor & Ovid Townships, Clinton County.

On 10 April 1996 the joint Clinton/Shiawassee County remonumentation peer group requested this position be monumented and recorded.

Approved by the joint Clinton/Shiawassee County Remonumentation peer group 22 May 1996.

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

## East 1/16th of the SE 1/4 of Section 36, T7N-RIW

Found record 6" x 8" x 12" Stone by Charles E. Hollister, Clinton County Surveyor, and raised with a 1/2" bar w/#12018 cap. E OF MICH

References:

6" Ash w/12018 tag 8 50 E 22.12'

Old fence corner post N & W w/12018 tag Old fence corner post, South w/12018 tag 1.0 North

South

7.27

14" Elm w/12018 tag 16" Twin Cherry w/12018 tag 16.45 N 20 W

6" Thorn apple w/12018 tag

Signed by

Dale 31 MAT

12018 Surveyor's Michigan License No.

CALDWELL

**PROFESSIONAL** 

**SURVEYOR** 

No.

12018 POFESSIO

MIE BOARD OF LAND SURVETORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983 ADAPTED FOR WORD PROCESSING MARCH, 1993

APPROVED BY CLINTON COUNTY PEER GROUP DATED 5/CC 196