

MAR 29 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich P.A. 1970

STATE OF MICHIGAN

COUNTY OF CRAWFORD

For corners in
Crawford County

LIBER

4

PAGE

50

Located in:

Corner Code #

1. Public Land Survey

T25N R1W L-13
T R
T R
T R

FILED FOR RECORD THIS
29th DAY OF Sept 1999 AT
9:00 am, IN LIBER 4
PAGE 50.
Sandra Moore.
Register of Deeds

Register of Deeds Stamp & File Number

I, Larry L. Cavanagh, in a field survey May 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in line 1 above was in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

A. Description of original monument and accessories and/or subsequent restoration:

JOHN BRINK 1839
SET POST
W. PINE 28° N70°E 26 LKS
Y. PINE 18° N51°W 70 LKS

NORM PARKER, RLS MAY 1975
LCRC L2, P16
FD NAT'L FOREST MON
6° W. OAK N85°W 9.35'
8° OAK NORTH 3.41'

T.N. CANADA 1937
FD REMAINS OF ORIGINAL BEARING
TREES
SET CONC MON 6" DIA X 24" BRASS
CAP & STEM
LOCAL BEARING TREES
6° W. OAK N32 1/4°E 57 LKS (NBT)
6° W OAK N29 3/4°W 80 LKS (NBT)
NEW BEARING TREES
7° W. OAK N27 1/2°E 48 LKS
9° N PINE N73 1/2°W 71 LKS

NORM PARKER, RLS MAY 1975
L145, P287
FD NAT'L FOREST MON
NO WITNESSES

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND GLO MONUMENT/FOREST SERVICE GUARD POST & TAG
FOUND PARKER WITNESSES FROM 1975
FOUND 10° W. OAK N25°E 31.6' TO CENTER OF TREE (POSSIBLE 1937 WITNESS)
FOUND 18° N. PINE N75°W 46.5' TO FACE (POSSIBLE 1937 WITNESS)

A PERPETUATION OF THE ORIGINAL GOVERNMENT CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

LEFT US-GLO MONUMENT IN PLACE 9' NORTH OF CENTERLINE OF TRAIL
WT: NAIL & TAG IN 7° W. OAK N306W 52.44'
NAIL & TAG IN 8° R OAK N7°E 3.35'
NAIL & TAG IN 7° W. PINE S34°W 37.24'
NAIL & TAG IN 7° W. PINE S43°E 41.70'
CARSONITE POST SOUTH 18.4'

CRAWFORD COUNTY
PEER GROUP APPROVAL
DATE Sept 10, 1999

Marvin E. Myers MEM
Marvin E. Myers, P.S.
County Surveyor



Signed by *Larry L. Cavanagh*
Surveyor's Michigan License NO. 17614

Date Sept. 14, 1999