

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Crawford

(County)

Located In

Corner Code #

1. Public Land Survey

T

R

2. Property Controlling  
in Section

S 8

T

25N

R 3W

7

3. Miscellaneous  
Property in Section

S 8

T

25N

R 3W

15

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on January 19, 2001 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

7- This corner position was not established during the original government survey

15- This corner position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

7- Established the Southeast corner of the Northeast quarter of the Northeast quarter of section 8 per B.L.M. instruction for the subdivision of a section.

15- Established the Southeast corner of the Southwest quarter of the Southwest quarter of section 8 per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

7- Set 5/8" X 32" rerod with P.S. cap #33981

Wit: 3" Oak	N80°E	15.04'
8" Jack Pine	N28°E	42.33'
18" Red Pine	West	65.67'
10" Spruce	S10°W	26.47'
Carsonite Post	North	1'±

15- Set 5/8" X 32" rerod with P.S. cap #33981

Wit: 8" White Pine	North	28.75'
10" Maple	N66°E	8.71'
8" Oak	S71°W	36.71'
10" Oak	S10°W	18.11'
½" iron	East	0.6'
Carsonite Post	North	1'±

Signed by:

Carl T Kiiskila

Date:

11-27-01

Surveyor's Michigan License No.:

33981

