

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Crawford
(County)
Located In
Corner Code #

1. Public Land Survey T 26 N R 1 W E-11
T 26 N R 1 W E-12
2. Property Controlling in Section S T R
S T R
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:
5. Private Claims:

I, Carl T. Kiiskila, in a field survey on October 6, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 and two black dots at intersections E-11 and F-12.

A. Description of original monument and accessories and/or subsequent restoration:

E-11 G.L.O. D.A. Pettibone 1852 set corner to sections 28,29,32 and 33. Wit: Pine 13" N44°W 15 1/2 links Pine 14" S58°E 50 links 1971 Kenneth J. Ostling R.L.S. #10068 found a concrete monument for corner, no witnesses given.
E-12 G.L.O. D. A. Pettibone 1852 set quarter section post Wit: Pine 14" N55°W 3.8 chains Pine 15" N06°W 4.46 chains 1971 Kenneth J. Ostling R.L.S. #10068 found a 3/4" pipe for corner, no witnesses given.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

E-11 Found concrete monument fitting K.J. Ostling's survey in section 32. E-12 Re-established the quarter corner common to sections 32 and 33 by doubling over the found 1" pipe set by Kenneth J. Ostling for the 1/16 corner 1/4 mile to the West with the center of section 1/2 mile to the West.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-11 Concrete monument Wit: 22" R. Pine S69°W 25.04' 10" Maple clump S18°W 12.41' 4" W. Pine S78°E 52.77' 6" Oak N86°E 64.51'
E-12 Set a 1" x 32" pipe with standard DNR Cap Wit: 9" Oak S50°E 56.18' 8" W. Pine N74°W 17.29' 12" W. Pine S25°W 32.16' 6" W. Pine N23°E 70.90' N-S fence West 60' Carsonite Post North 1'±

Signed by: Carl T Kiiskila
Surveyor's Michigan License No.: 33981

Date: 10/17/05

