## LAND CORNER RECORDATION CERTIFICATE

C.... (

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY_	T26 _ , R3 _ V	F-11	
2. PROPERTY CONTROLL- ING IN SECTION-	33 ,T. 26 N., R. 3 W	. 4	-
3. MISCELLANEOUS PROPERTY IN SECTION .	33 ,T. 26 N. R. 3	F-11/5	
4. LOT NO, 1	RECORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned re-established, monumented, and rules therefore as required Bureau of Land Management and 5 above were, in a field as expressed below and in concerned of a Court of law:	in lines 1 and 2 above were, in re-monumented, recovered or red in the current manual of surt or by a decree of a court of last account of las	a field survey on April restored as expressed below a vey instructions of the United w. Furthermore, that the corn, 1971, found, recovered, re Michigan State Board of Reg	s of P.A. 74, Michigan P.A. of 1970, 30, 19_76, established, and in conformance with regulations. States Department of the Interior, mer points mentioned in lines 3, 4 estored, established or re-established istration for Land Surveyors or, by a
F-11 Previously estab  4 Set by standard	idence found and/or method ap lished in 1959 survey; survey procedure for su	restored and remarked abdivision of sections	d this date.
F-11 Previously estab	lished in 1959 survey; survey procedure for so	restored and remarked abdivision of sections	d this date.
F-11 Previously estab  4 Set by standard  5-11/5 Set by standard  C. Description of monuments	lished in 1959 survey; survey procedure for susurvey procedure for the	restored and remarked abdivision of sections the subdivision of sections abbished to perpetuate locating	the position of the corner:
F-11 Previously estab  4 Set by standard  5-11/5 Set by standard	survey procedure for survey; survey procedure for the survey;  Set 3' of 1½'' pred-top post 6'' W. Oak NO:  2 7'' R. Oak NO:	restored and remarked abdivision of sections the subdivision of sections abbished to perpetuate locating	the position of the corner:
F-11 Previously estab  4 Set by standard  C. Description of monumer F-11  DNR mon. with brass caremark witnesses from 7/16/59 survey 8" W. Oak S13°W 12. 7" R. Oak East 34.	survey procedure for survey; survey procedure for the survey;  Set 3' of 1½'' pred-top post 6'' W. Oak NO:  2 7'' R. Oak NO:	restored and remarked abdivision of sections the subdivision of sections ablished to perpetuate locating pipe & Set 7" & Set 9°W 21.4 8" & Set 9°.1	the position of the corner:  F-11/5 3' of 1½" pipe V. Oak N10°E 22.4 V. Oak S80°E 5.3  KENNETH J. OSTLING LAND
F-11 Previously estab  4 Set by standard  5-11/5 Set by standard  C. Description of monumer F-11  DNR mon. with brass caremark witnesses from 7/16/59 survey 8" W. Oak S13°W 12. 7" R. Oak East 34.	lished in 1959 survey; survey procedure for survey procedure for the survey;  Set 3' of 1½" pred-top post 6" W. Oak NOS 7" R. Oak NOS 65	restored and remarked abdivision of sections the subdivision of sections abbished to perpetuate locating pipe & Set 7"   Set 4°E 9.1	the position of the corner:  F-11/5 3' of 1½" pipe V. Oak N10°E 22.4 V. Oak S80°E 5.3  KENNETH J. OSTLING LAND
F-11 Previously estab  4 Set by standard  5-11/5 Set by standard  C. Description of monumer F-11  DNR mon. with brass caremark witnesses from 7/16/59 survey 8" W. Oak S13°W 12. 7" R. Oak East 34.	survey procedure for survey; survey procedure for survey procedure for the survey procedure for	restored and remarked abdivision of sections the subdivision of sections abbished to perpetuate locating pipe & Set 7"   Set 4°E 9.1	the position of the corner:  F-11/5 3' of 1½" pipe V. Oak N10°E 22.4 V. Oak S80°E 5.3  KENNETH J. OSTLING LAND
F-11 Previously estab  4 Set by standard  -11/5 Set by standard  C. Description of monumer F-11  DNR mon. with brass caremark witnesses from 7/16/59 survey 8" W. Oak S13°W 12. 7" R. Oak East 34.  SIGNED BY Common Survey  SURVEYOR'S MICHIGAN FOR STATE AND UNITE	survey procedure for survey; survey procedure for the survey procedure	restored and remarked abdivision of sections he subdivision of sections ablished to perpetuate locating pipe & Set 7"   90W 21.4 8"   90H 21.4	the position of the corner:  F-11/5 3' of 1½" pipe V. Oak N10°E 22.4 V. Oak S80°E 5.3  KENNETH J. OSTLING LAND