

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:  
Crawford  
(County)

Located In

Corner Code #

1. Public Land Survey	T	26N	R	4W	C1
	T	27N	R	4W	C13
2. Property Controlling in Section	S	T	R		
	S	T	R		
3. Miscellaneous Property in Section	S	T	R		
	S	T	R		

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Craig W. McVean, in a field survey on September 20, 2000 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

## A. Description of original monument and accessories and/or subsequent restoration:

C1 & C13 – GLO – Set post – J.H. Mullett – 1839

Pine 12" N28°W 16 L.

Pine 10" N20°E 29 L.

- GLO – T26N R4W – A.P. Brewer - 1852

Y. Pine 12" S83°45'W 17' L.

S. Pine 6" S63°E 56 L.

- GLO - T27N R4W – A.P. Brewer - 1852

S. Pine 9" N56 ½°W 81 L.

S. Pine 12" N56°E 70 L.

- DNR corner record – 1955 & 1956 – K.J. Ostling – Set 1" pipe w/ 4" brass cap by single proportion between Houghton Tile East (E13) & USGS Town corner West. A very small hub was found less than 2 Link West when placing the post.

6" J. Pine N17°E 23 L.

5" J. Pine S62°E 32 L.

## B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

C1 & C13 – Standard section corner common to Sec. 5 & 6, T26N, R4W & Sec. 31 & 32, T27N, R4W – Fd. 4" DOC (DNR) brass cap on 1" iron pipe per DNR record. CL of E-W Bit. Rd. is 67' N. DOC (DNR) Mon. accepted as a careful & faithful re-establishment of the position of the original corner.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C1 & C13 – 4" DOC (DNR) brass cap on 1" iron pipe.

SW 1.3' to face Fd. Cedar post.

Set Blue Carsonite Post 1' N.

S72°W 151.61' to set N & T in S side 5" J. Pine scribed 'XBT'

N28°E 130.69 to set N & T in W side 8" J. Pine scribed 'XBT'

N8°W 29.35' to set N & T in E side 2" J. Pine

N79°E 102.61' to set N & T in S side 3" J. Pine



Signed by:

*Craig W. McVean*

Date:

*4/11/2001*

Surveyor's Michigan License No.:

39088