

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Crawford
(County)

Located In

Corner Code #

1. Public Land Survey T R
T R
2. Property Controlling in Section S 32 T 27N R 3W 8
S 32 T 27N R 3W 11
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on December 1, 2006 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

8- 1976, Liber 174, page 292 C.E. Ostling R.L.S. #12026 set a 1/2" bar for corner.

11- 1965 C.E. Ostling R.L.S. #12026 set a concrete monument for the Northeast corner of the plat of East Branch Estates.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

8- Found 3/8" bar as set by C.E. Ostling fitting the proper procedure for the subdivision of a section.

11- Found concrete monument as set by C.E. Ostling fitting the proper procedure for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

8- Replaced 3/8" bar with 5/8" X 32" rerod with P.S. cap #33981

11- Found concrete monument

Wit: 11" R. Pine S14°W 8.95'
22" R. Pine N76°E 28.42'
7" R. Pine N56°W 6.64'
6" R. Pine S47°E 6.81'
1/2" Bar N86°W 21.50'

Wit: 6" White Pine S36°E 18.66'
18" Twin Red Pine N73°E 24.57'
9" Oak N10°W 21.28'
8" R. Pine N78°W 32.31'
Blue Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

8-10-09

Surveyor's Michigan License No.:

33981

