

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. <u>27</u> N. R. <u>3</u>	<u>L-2; L-3</u>
2. PROPERTY CONTROLLING IN SECTION <u>1</u>	T. <u>27</u> N. R. <u>3</u>	<u>8</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S. R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 15, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

L-2 Set corner by standard survey procedure for the subdivision of sections.

L-3 Found 1/2" iron bar as restored in previous survey of this section by O.S.I. from Newman witness.

8 Set by standard survey procedure for subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-2	L-3	8
Set 1"x30" Pipe & red-top post	Replace 1/2" rebar w/DNR mon. & red-top post	Set 1" x 30" Pipe
9" J. Pine S40°W 140.7	11" J. Pine S32°E 102.4	Nail in 8" J. Pine N87°E 36.2
11" J. Pine S10°W 142.0	2" J. Pine S50°W 128.9	Nail in 11" J. Pine N33°E 23.05

SIGNED BY

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

