

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF-- LOCATED IN-- CORNER CODE NUMBER

1. PUBLIC LAND SURVEY T 27 N. R. 3 S. J-5; K-4

2. PROPERTY CONTROLLING IN SECTION 11 T 27 N. R. 3 S. 9; 16

3. MISCELLANEOUS PROPERTY IN SECTION T. S. R. W.

4. LOT NO. RECORDED PLAT

5. PRIVATE CLAIMS

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on October 8, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and in subsequent restorations

C. (continued)

16
Set 5/8" Rod w/RLS Cap
& Cedar Post
3" Tamarack N76°W 36.6
2" Tamarack N25°E 17.58

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner

- 5 Fd. brass cap monument in place as set in 1930's survey of State park, probably by Granger. Fits computed position acceptably.
- 4 Fd. park monument as established in 1930's survey of park boundary, probably by G. Granger.
- 9 Set by standard survey procedure for the subdivision of sections.
- 6 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

J-5	K-4	9
Left park monument in place	Left park monument in place,	Set 5/8" rod w/RLS Cap
8" J. Pine N14°E 10.75	set cedar post	& cedar post
8" J. Pine S85°W 25.4	5" Balsam N21°E 32.95	Nail in 4" W. Pine S15°W 25.1
	2" Balsam N86°W 14.95	Nail in 3" J. Pine S75°W 42.65

SIGNED BY Kenneth J. Ostling

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES.

SIGNED BY _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____
MICHIGAN REGISTERED LAND SURVEYOR

DATE

DATE

DATE



(SEAL)

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

CRAWFORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET