

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>27</u> N. R. <u>4</u> W.	<u>A-5</u> , A-6
2. PROPERTY CONTROLLING IN SECTION <u>18</u>	T. <u>27</u> N. R. <u>4</u> W.	<u>9</u> ; <u>12</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S. R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on March 7, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. - Description of original monument and accessories and/or subsequent restoration:~~
C. (continued)

12
Set 5/8" Rod w/RLS Cap
and cedar post
4" J. Pine S37°E 15.11
3" W. Pine N48°E 5.61

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- A-5(A) Restored from U.S.B.T. stumps by M. Schaaf in 1940's survey. Recovered and replaced under direction of D. L. DeLaMater in 1951. (B) Rewitnessed previous DNR corner for recording.
- A-6 Adjusted previous corner slightly to conform to proportionate measurement.
- 9 Set corner by standard survey procedure for the subdivision of sections.
- 12 Set corner by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-5	A-6	9
Fd. DNR mon. & red-top post	DNR mon. in place from	Set 5/8" Rod w/RLS Cap
6" J. Pine S79°W 47.36	1965 survey	and cedar post
11" J. Pine N26°W 3.16	6" R. Pine N72°E 21.68	4" Spruce S83°E 11.24
4" J. Pine S46°E 55.9	7" R. Pine N15°W 17.73	7" J. Pine S45°E 23.33

SIGNED BY

Kenneth J. Ostling

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES.

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

DATE

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

CRAWFORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET