

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Crawford

(County)

Located In

Corner Code #

1. Public Land Survey

T

R

2. Property Controlling
in Section

S 35

T

28N

R

3W

4

3. Miscellaneous
Property in Section

S 35

T

28N

R

3W

8

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on February 12, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

4 - NW 1/16 Cor., Section 35, T28N, R3W

8 - CW 1/16 Cor., Section 35, T28N, R3W

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

4 - NW 1/16 Cor., Section 35, T28N, R3W

8 - CW 1/16 Cor., Section 35, T28N, R3W

Set 5/8"x34" CIR#33981 per standard BLM procedure.
Found no other evidence to dispute the location for the corner.

Set 5/8"x34" CIR#33981 per standard BLM procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

4 - NW 1/16 Cor., Section 35, T28N, R3W

8 - CW 1/16 Cor., Section 35, T28N, R3W

5/8"x34" CIR#33981

Wit: N32°E 32.25' to set N&T on SE side 12" S. Maple
East 27.00' to set N&T on S side 9" S. Maple
S20°E 9.45' to set N&T on W side 9" Elm
S67°W 5.75' to set N&T on SE side 13" S. Maple
East 11.4' to S end of N-S fence
Found remains of fence running W from corner
Set Blue Carsonite Post w/loc. tag 0.5' North

5/8"x34" CIR#33981

Wit: N66°W 33.85' to set N&T on S side 9" S. Maple
N27°E 40.46' to set N&T on NW side 12" S. Maple
N77°E 28.05' to set N&T on S side 12&16" Twin
S. Maple
S52°W 20.55' to set N&T on NW side 10" S. Maple
N65°E 1.13' to fd. 1/2" CIR#17614 (Did not accept)
Found remains of wire fence running N&W from cor.
Set Blue Carsonite Post w/loc. tag 1' North

Signed by:

Carl T. Kiiskila

Date:

1-6-10

Surveyor's Michigan License No.:

33981

