

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Crawford Located In _____ Corner Code # _____
(County)

1. Public Land Survey T _____ R _____
T _____ R _____
2. Property Controlling in Section S 20 T 28N R 3W 8
S 20 T 28N R 3W 11
3. Miscellaneous Property in Section S _____ T _____ R _____
S _____ T _____ R _____

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on August 19, 2008 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

8-This corner position was not established during the original government survey. 11- This corner position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

8- Established the Northwest corner of the Northeast quarter of the Southwest quarter of section 20 as per B.L.M. instructions for the subdivision of a section. 11- Established the Northeast corner of the Southwest quarter of the Southwest quarter of section 20 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

8- Set 5/8" X 32" rerod with P.S. cap #33981
Wit: Set nail and tag in South side of a 14" and 10" Twin Maple S12°W 17.25'
Set nail and tag in West side of a 9" Twin Beech N39°W 7.79'
Set nail and tag in North side of a 13" Maple N54°E 18.41'
Set nail and tag in East side of a 8" Maple S44°E 13.94'
Set Carsonite post North 1'±

11- Set 5/8" X 32" rerod with P.S. cap #33981
Wit: Set nail and tag East side 10" Maple N18°W 8.78'
Set nail and tag South Side 6" Maple N62°E 18.13'
Set nail and tag North side of 9" Maple S65°E 16.49'
Set nail and tag Southeast side 14" Beech S35°W 6.29'
Carsonite Post north 1'±

Signed by:

Carl T. Kiiskila

Date:

6-23-09

Surveyor's Michigan License No.:

33981

