

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Charlevoix

(County)

Located In

Corner Code #

1. Public Land Survey	T	32N	R	5W	H-11
	T	32N	R	5W	H-12
2. Property Controlling in Section	S	T	R		
	S	T	R		
3. Miscellaneous Property in Section	S	T	R		
	S	T	R		

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 27, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

H-11 G.L.O. William Burt 1850 Set Cedar quarter section post. Wit: W. Pine 10" N32°E 65 links Cedar 5" S71°W 10 links

H-12 June 1904 E.K. Robinson set the center of section 34 at the intersection of the North-South and East-West quarter lines. Type of monument and witnesses were not given.

June 1904 E.K. Robinson used the North ¼ corner of section 34 to set the center. Type of monument and witnesses not given.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

H-11 Found 2" pipe fitting E.K. Robinson distances in section 34.

H-12 Found 2" pipe fitting E.K. Robinson distances in section 34.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-11 Found 2" pipe added P.S. cap #33981

Wit: 10" Cedar	S55°W	12.60'
9" Cedar	S59°E	6.54'
12" Cedar	N42°E	14.08'
7" Cedar	N08°W	9.78'
Blue Carsonite Post	North	1'±

H-12 Found 2" pipe

Wit: 8" Maple	N88°W	40.12'
12" Maple	S12°E	18.42'
10" Maple	N76°E	10.00'
8" Maple	N12°W	22.99'

Signed by:

Carl T. Kiiskila

Date:

8/10/05

Surveyor's Michigan License No.:

33981

