98 SEP 15 AN 10: 04

For corners in	Fili	ng Requirement	t of Act 74, Mich. I	P.A. 1970		13. Carlos
Charlevoix	Located In:	Corner Cod	lo #		REGISTI	ER OF DEEDS
(County)	Located III.	Corner Cou	ie #			
1. Public Land Survey	T_32R T_31R		MC E. OF B-13 MC E. OF B-1		*028	)
<ul><li>2. Property Controlling In Section</li><li>3. Miscellaneous Property in Sec.</li></ul>	S TR S TR S TR			R		Stamp & File Numb
4 Int No. Reco	rded Plat					
4. Lot No, Reco 5. Private Claims	TOOU FIAL			1 A	BCDEF	GHIJK
	•			2	6	
Wayne E. Boss		Turne 0	Q.	3	<del></del>	
requirements of P.A. 74, Michiga	, in a field survey on an P.A. of 1970, the come	r points mentioned in	lines 1 and 2 shove w	ora in	7	10-11-
conformance with regulations and United States Department of the I that the corner points mentioned Board of Land Surveyors or by recovered, found as expressed be	rules therefore as required hterior, Bureau of Land Mi in fines 3, 4 and 5 above y a Decree of a Court of	d in the current manus anagement or by a dec vere in conformance v	of survey instructions oree of a Court of Law at with the rules of the Mic	of the 5 higan	10-17-16-	
NOTE: Not more than 2 com	ers, all in the same town	and range may be	recorded	و		
on this certificate.		and range, may be	recorded	10 -3	02928	2 <sup>7</sup> 262
				11	<del>                                     </del>	<del> - - - - </del>
				12 -3	1	3 <del>'43'53'</del> ,
SET POST V HEMLOCK	R EAST OF B-13	TY SURVEYOR E 28 LINKS	SEPTEMBER 1 A. LESTER DR FOUND WITNE PLACED CONC	AGOO, P.S. ESS STUMPS CRETE MON OF LINCOLN I ANTRIM C	UMENT V WOODS PLAT OUNTY REGIST	TER OF DEEDS
B. Description of corner evide	nce found and/or meth	ad applied in resta	ring ar recetabliching	COTDAT:		
MEANDER CORNER		od applied ill restor	and or recardnishing	Comer.		
FEB. 19, 1998 5" MAPLE S 10" STUMP S 12" POPLAR 10" POPLAR 10" BASSWO 93'+/- FROM B-13 TO MEA	FOUND CONCR 11*E 6.83' TO CENT 180*W 12.67 TO CEN STUMP N50*W 2.83' STUMP 01*E 8.33' T OD N40*E 26.85' TO WEST EDGE OF LAI NDER CORNER GLO E OF OLD CORNER	ER FOUND NAII TER FOUND NA TO CENTER FOUN CENTER FOUN CENTER FOUN KE D 23.72 CHAINS	L IN NORTH FACE IL IN EAST FACE DUND NAIL SE FA ND NAIL SOUTH D BLAZE SW FAC	ë : ACE FACE CE	APP Signature /// Date: _/	
C. Description of monument for	corner and accessorie	s established to pe	rpetuate locating the	position of the	ecorner: sug	do_
MEANDER CORNER E 5"' MAPLE S11 10" STUMP S86 12" POPLAR S1 10" POPLAR S1 10" BASSWOOI 18" HEMLOCK	AST OF B13 CONCI 1*E 6.83 SET NAIL & D*W 12.67' TO CENT FUMP N50*W 2.83' TO FUMP N01*E 8.33 TO D N40*E 26.85' SET N75*E 58.62' SET N	RETE MONUME L TAG TER TO CENTER O CENTER NAIL & TAG	NT AS FOUND	TICENSES AND THE	WAYNE E. BOSS PROFESSIONAL SURVEYOR NO. 20703	W. C.
AND IS ACCEPTED A	OA CAREPUL & KA	ijhrul reest/	ABLISHMENT OF	THE POSITI	ON OF THE OR	IGINAL CORNER
Signed by // //	~cus	<u> </u>	Date	Hug. 2	+ 1998	<b>3</b>
Surveyor's Michigan Lipense No.	20703					<del></del>