

FEB 22 2001

SECTION

CHANDLER TOWNSHIP

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF CHARLEVOIX  
RECORD

00 DEC -8 PM 12: 24

*Charles M. Jost*  
REGISTER OF DEEDS

CHARLEVOIX  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 33N R 4W  
T R  
T 33N R 5W  
T R  
T R

2. Property Controlling  
in Section

S T R  
S T R

3. Miscellaneous  
Property in Sec.

S T R  
S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, **JAMES E. EVANS**, in a field survey **APRIL 5**, 2000 do hereby state that requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

A-5 SECTION CORNER COMMON TO SECTIONS 7 & 18 T33N -R4W AND SECTIONS 12 & 13 T33N-R5W

GLO: SET POST Carl F. Roser PS #12028 LCRC 1-12-1982  
Sugar 24" S40E 15 lks (9.90') Found Schaaf monument from 1930's and replaced with DNR monument  
Hemlock 24" N50'W 18 lks (11.88') and cedar post.  
May 23, 1840 7" Ironwood South 15.1 (1)  
By: John Mullett D. S. 3" Twin Maple N30'E 12.7 (2)  
4" Maple S75'E 35.0' (3)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner

A-5 SECTION CORNER COMMON TO SECTIONS 7 & 18 T33N -R4W AND SECTIONS 12 & 13 T33N-R5W

Found DNR monument and cedar post

Distance to A-4 2668.51' (GLO = 2640.0' DNR = 2668.58')

Distance to A-6 2658.67' (GLO = 2640.0 DNR = 2658.67' E.A. Robinson = 2677.1)

Charlevoix Co. Surveyor  
APPROVED

Signature *Mary C. Feindt*  
Date: *Dec 7, 2000*

C. Description of monument for corner and accessories established to perpetuate location the position of the corner:

A-5 SECTION CORNER COMMON TO SECTIONS 7 & 18 T33N -R4W AND SECTIONS 12 & 13 T33N-R5W

FOUND DNR MONUMENT AND CEDAR POST

7" Ironwood S 2' W 15.26' Set nail & cap #22431 in blaze mark in SW side. (1)  
9" Twin Maple N 32' E 12.75' Set nail & cap #22431 in blaze mark in South side. (2)  
6" Maple S 74' E 35.16' Set nail & cap #22431 in blaze mark in SW side. (3)  
9" Tri Ironwood N 15' W 28.53' Set nail & cap #22431 in East side.

And is accepted as the best available evidence of the position of the original corner.

Signed by *James E. Evans*  
Surveyor's Michigan License No 22431

Date 12-07-00

