

FEB 22 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

CHANDLER TOWNSHIP

CHARLEVOIX  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 33N R 4W A-2  
T R  
T 33N 5W 11-20 ✓  
T R  
T R

2. Property Controlling  
In Section

S T R  
S T R

3. Miscellaneous  
Property in Sec.

S T R  
S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, JAMES E. EVANS, in a field survey APRIL 5, 2000 do hereby state that requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

- A. Description of original monument and accessories and/or subsequent restoration:  
A-2 QUARTER CORNER COMMON TO SECTION 6 T33N-R4W AND SECTION 1 T33N-R5W  
GLO: SET QUARTER SECTION POST Michigan Conservation Dept.  
Beech 18" S15W 17 lks (11.22') 12-12-1961 by Kenneth Ostling  
Sugar 6" N33'E 6 lks (3.96') Set 1" Pipe with 4" Aluminum Cap  
May 23, 1840 4" Hemlock S78'W 29.5' (1)  
By: John Mullett D. S. 5" Elm N27'W 34.4'

John Ferguson PS #24595  
LCRC Liber 2 Page 156 dated 6-17-1982  
Set 1 1/2" pipe & cap at position indicated by  
1961 Conservation Dept.  
8" Basswood North 23.7' (2)  
8" Maple N45'W 24.95' (3)  
8" Basswood S40'W 12.5' (4)  
5" Hemlock S78'W 29.5' (1)

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner  
A-2 QUARTER CORNER COMMON TO SECTION 6 T33N-R4W AND SECTION 1 T33N-R5W

FOUND FERGUSON PIPE AND CAP #24595 10 FT. WEST OF TWO TRACK ROAD.

REPLACED WITH CHARLEVOIX COUNTY MONUMENT

Distance to A-1 2734.70' (GLO = 2722.50' GLO Proration = 2733.36' Ferguson = 2733.51')

Distance to computed A-3 2650.64' (GLO = 2640.0 GLO proration = 2650.53' Ferguson = 2650.39')

- C. Description of monument for corner and accessories established to perpetuate location the position of the corner:  
A-2 QUARTER CORNER COMMON TO SECTION 6 T33N-R4W AND SECTION 1 T33N-R5W

REPLACED PIPE WITH CHARLEVOIX COUNTY MONUMENT

8" Maple N 01° W 23.59' Set nail & cap #22431 in blaze mark in SW side (2)  
10" Maple N 74° W 24.92' Set nail & cap #22431 in blaze mark in East side (3)  
8'-10" Twin Maple S 40° W 12.55' Found nail in blaze mark in NE side (4)  
24 Maple S 62° E 32.29' Set nail & cap #22341 in SW side

And is accepted as the best available evidence of the position of the original corner.

Signed by James E. Evans  
Surveyor's Michigan License No 22431

Date 12-07-00

STATE OF MICHIGAN  
COUNTY OF CHARLEVOIX  
RECEIVED FOR RECORD

00 DEC -8 PM 12: 21

*Caroline M. Jostberg*

REGISTER OF DEEDS

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5			4		3		2		1	
3													
4	7		8			9		10		11		12	
5													
6	18		17			16		15		14		13	
7													
8	19		20			21		22		23		24	
9													
10	30		29			28		27		26		25	
11													
12	31		32			33		34		35		36	
13													

Charlevoix Co. Surveyor  
APPROVED  
Signature Mary C. Farnell  
Date: Dec 7, 2000

