

SAME AS L.3 Pg. 291

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
RECEIVED

99 DEC 17 PM 12:50

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

CHARLEVOIX
(County)

Located In:

Corner Code #

1. Public Land Survey

T. 33NR 7W

A-12

T. R.

T. R.

T. R.

2. Property Controlling
in Section

S.

T. R.

S.

T. R.

3. Miscellaneous
Property in Sec.

S.

T. R.

S.

T. R.

Charles M. Justice

REGISTER OF DEEDS

RECORDED

FEB 01 2000

SECTION

Register of Deeds Stamp & File Num

4. Lot No. , Recorded Plat

5. Private Claims

I, ARTHUR R. RANGER, in a field survey on NOV. 12, 1999
do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in
lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual
of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a
decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in
conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law;
established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
CORNER COMMON TO SEC. 36, T.33N., R.8W., AND SEC. 31, T.33N., R.7W.

1840-John Mullett set a Qr. Sec. Post and witnesses: Spruce 10" N74°W 72 lks; No other bearing available.
1903-Robinson established a temporary position for the corner, could not find corner. Took a bearing on a
Tamarack 8" S73°W 8.25'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
CORNER COMMON TO SEC. 36, T.33N., R.8W., AND SEC. 31, T.33N., R.7W.

1999-Arthur R. Ranger found no evidence of the corner.
Set a Charlevoix County Monument half way between M-11 and M-13.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

CORNER COMMON TO SEC. 36, T.33N., R.8W., AND SEC. 31, T.33N., R.7W.

(SET A CHARLEVOIX COUNTY MONUMENT)

Witnesses:

9" Tamarack East 33.18'
12" Tamarack N27°E 16.69'
12" Tamarack N17°E 34.77'
4" Tamarack N14°W 31.75'

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Arthur R. Ranger

Date 12/16/99

Surveyor's Michigan License No. 31601

Charlevoix Co. Surveyor
APPROVED
Signature Mary C. Freundt
Date: Dec. 16, 1999



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1996

LIBER U03 PAGE 297