

Sheet 9 of 17 Sheets

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
RECEIVED FOR RECORD

96 DEC 11 PM 2:57

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970For corners in
Charlevoix

Located in:

Corner Code ##

1. Public Land Survey

2. Property Controlling
In Section3. Miscellaneous
Property in Sec.

T 32N	R 7W	E-1
T 33N	R 7W	E-13
T	R	
T	R	
S	T	R
S	T	R
S	T	R
S	T	R

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____REGISTER OF DEEDS
SURVEY &
REMONUMENTATION

FEB 19 1998

Register of Deeds Stamp

I, Wayne E. Boss, in a field survey on OCTOBER 18, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-1	GLO JUNE 1839 JOHN HODGSON SET COR. POST	3. BEECH 10 N86E 41 4. MAPLE 3 N32 1/4 W 55	5. APPLE 7" S 42 1/4 E 129 6. SUGAR WEST OF THIRTEEN 12" N81 1/4 W 68.51K
	1. BEECH 7 N64W 7 2. BEECH 14 N49E 14	E.K. ROBINSON MAY 1895 SURVEY REESTABLISHED CORNER BY PROPORTIONATE MEASUREMENT & SET A 20 X 16 X 8 IN. STONE WITH A SINKING 2 STONES (O) CUT IN TOP.	T IR. SET BY UNKNOWN. FITS E.K.R. WIT. 6. SUGAR 42" N81W 45.2' CORNER USED IN SUBSEQUENT SURVETS
	W. MILLER AUG 1883 COR. RENEWED BY SINKING 2 STONES		JOHN FERGUSON DEC. 1978. L.C.R.C. L2 P.91 7. 37" MAPLE N84W 39.02' (SEE BACK)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-1 ALUM. SPIKE PD. OVER 18" BOLT OVER 2" WELL POINT WHICH FITS E.K.R. WIT.#6.
6. 42" MAPLE N81W 45.21
7. 42" MAPLE N77W 38.96
11. 40" MAPLE N25W 70.14'
12. POWER POLE S 70W 97.83'
13. S61E 77.14 TWIN 10" APPLE 77.29'

Charlevoix Co. Surveyor
APPROVED
Signature Wayne E. Boss
Date: Nov. 13, 1996

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-1 & E-13 E-1 T32N-R7W CORNER COMMON TO E-13 T33N-R7W
CHARLEVOIX CO. MON. SET.

6. 42" MAPLE N81W 45.21

7. 42" MAPLE N77W 38.96

11. 40" MAPLE N25W 70.14'

12. POWER POLE S 70W 97.83'

13. S61E 77.14 TWIN 10" APPLE 77.29'

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

Surveyor's Michigan License No.

20703

LIBER

003

PAGE

71

Date

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

Sheet 10 of 17 sheets

3610.0
19.000.0
0.0SURVEY &
REMONUMENTATION

FEB 19 1998

SECTION

A. con't

8. TELE. RISER S24W 60.9'
9. 15" APPLE S61E 59.45'
10. TELE. RISER S26E 61.80'

L. FEINDT
13. S61E 77.23" TWIN 10" APPLE
14. S35E 45.84" CTR. SIGN POST

N. DEYOUNG 1975 & 1983
7. N85W 39.00' 42" MAPLE
9. S60E 59.35' 10" APPLE
11. N36W 70.30' 40" MAPLE
12. S76W 97.53' POWER POLE

J. FERGUSON 1987, L.C.R.C. L.2, P.218.
7. 36" MAPLE N77W 38.9'
9. ELM STUMP S57E 59.3'
11. 36" MAPLE N25W 70.2'
12. POWER POLE S70W 97.8'