

99 SEP 16 PM 2:29

*Charles B. Jost*  
REGISTER OF DEEDS

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Charlevoix

(County)

Located In:

Corner Code #

1. Public Land Survey

T 33NR 8W

T R

T 32NR 8W

T R

T R

T R

T R

T R

H-13

H-1

2. Property Controlling  
in Section

3. Miscellaneous  
Property in Sec.

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Wayne E. Boss

I, \_\_\_\_\_, in a field survey on June 98, 19 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

H-13 MAY & JUNE 1839

JOHN HODGSON, DEPUTY SURVEYOR  
SET POST 40 CHAINS WEST OF SEC. POST  
SUGAR 30 INCH N57°E 7 LINKS  
BEECH 7 INCH N29°W 35 LINKS

JULY 21, 1978 NB DEYOUNG, P.S.  
FOUND 3/4" PIPE IN EAST WEST FENCE LINE  
10" MAPLE S10°E 4.15'  
5" MAPLE S30°E 4.38'  
5" MAPLE N15°E 19.7'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-13 APRIL 15, 1999

FOUND 1" O.D. PIPE IN REMAINS OF E-W FENCE  
16" MAPLE S10°E 4.15' FOUND BLAZE  
5" MAPLE S30°W 4.38' FOUND BLAZE  
5" MAPLE N15°E 19.7' FOUND BLAZE

I-13 TO H-13 GLO 40 CHAINS (2640'), NB DYOUNG 2647.88', MEASURES N87°59'05"W 2645.38'  
H-13 TO G-13 GLO 40 CHAINS (2640') MEASURES N88°11'56"W 2613.04'

Charlevoix Co. Surveyor

APPROVED

Signature *Wayne E. Boss*  
Date: September 16, 1999

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-13 PLACED CHARLEVOIX COUNTY STEEL MARKER

16" MAPLE S10°E 4.15'  
8" MAPLE S30°W 4.38'  
5" MAPLE N15°E 19.7'  
5" MAPLE N56°W 22.89' SET NAIL & TAG

AND IS ACCEPTED AS A CAREFUL & FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER

Signed by

Surveyor's Michigan License No. 20703

Date

8/23/99

LIBER U03 PAGE 263