

Survey
Monumentation

MAY 1997
COMMISSION

RE MONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED
FOR RECORD

96 NOV 25 PM 1:00

James D. Gray
CLERK/REGISTER
CHEBOYGAN COUNTY, MICHIGAN

Cheboygan
(County)

Located In: Corner Code #

1. Public Land Survey T 34N R 3W M-13
T R
T 33 R 02 A-01
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Brian K. Fullford, in a field survey on August, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.	1973 Recorded Survey	1976 Unrecorded Survey	1995 Unrecorded LCRC
Set Township Corner	Liber 336, Page 433	By George Henning #2240	By Norm Quaine #33984
10" Sugar N25°E 12 Links	By R.C. Dunn #12020	1" Pipe in 2" Pipe	1" Pipe inside 2" Pipe
8" Sugar S65°W 10 Links	Survey Showing Tie to Section Corner	MSHD Witness Tags	N76°E 15.11' 11" Spruce
			S73°E 23.35' 9" Ironwood
			S44°E 23.22' 17" Aspen
			S10°W 19.10' 22" Aspen

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1" Pipe Inside 2" Pipe
11" Spruce N76°E 14.93'
9" Ironwood S73°E 22.53'
17" Aspen S44°E 21.85'
22" Aspen S10°W 18.02'



LIBER 010 PAGE 203

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-13 Found 1" Pipe Inside 2" Pipe #15410. Replaced with 5/8" x 36" Bar with Remonumentation Cap. Accepted as a careful & faithful re-establishment of the position of the original corner.

11" Spruce N76°E 14.93'
9" Ironwood S73°E 22.53'
17" Aspen S44°E 21.85'
22" Aspen S10°W 18.02'

THIS CORNER IS ALSO DESIGNATED AS CORNER CODES #A-13, IN T34N-R2W, #A-1, IN T33N-R2W AND #M-1, IN T33N-R3W.

Signed by *B. K. Fullford*
Surveyor's Michigan License No. 41099
Brian K. Fullford, PS

Date 10/22/96

