

SURVEY & REMONUMENTATION

MAY 05 1997

RE MONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
COMMISSION

<u>Cheboygan</u>	Located In:	Corner Code #
(County)		
1. Public Land Survey	T <u>33N</u> R <u>3W</u>	M-11
	T <u>33</u> R <u>02</u>	<u>A-11</u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	

RECEIVED
FOR RECORD

96 NOV 25 PM 12: 55

Joanna Gray
CLERK/REGISTER
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Brian K. Fullford, in a field survey on August, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	19	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.	1960 LCRC
Set Section Corner Post	County Surveyors Corner Record
16" Hemlock S66°E 11 Links	Dean DeLamater #5778
12" Hemlock N62°W 12 Links	Fnd 1 1/2" Flat Iron
	7" Poplar N28°E 9.47'
	7" Poplar S77°W 15.95'
	8" Poplar S54°W 29.00'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fnd 1 1/2" Flat Iron
7" Poplar N28°E 9.47' (Fnd-Dead)
8" Poplar S54°W 29.00' (Fnd-Dead)



LIBER 010 PAGE 199

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-11 Fnd 1 1/2" Flat Iron, Replaced with 5/8"x 36" Bar & Remonumentation Cap. Accepted as a careful & faithful re-establishment of the position of the original corner.

8" Poplar N11°E 8.23' Set Tag
10" Poplar N76°E 13.52' Set Tag
14" Poplar N66°W 42.02' Set Tag
10" Poplar S02°W 25.14' Set Tag
Between N & S Bound I-75 400' South of Mile Marker #296

THIS CORNER IS ALSO DESIGNATED AS CORNER CODE #A-11, IN T33N-R2W.

Signed by Brian K. Fullford
Surveyor's Michigan License No. 41099

Date 10/22/96

Brian K. Fullford, PS

