

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
CHEBOYGAN

(County)

Located In:

Corner Code ~~##~~

1. Public Land Survey

T 33N R 02W

C-9, C-10

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, CARL T. KIISKILA, in a field survey on AUGUST 14, 19 96,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:
C-9 C-10

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY,
AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B"
BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
C-9 C-10

FOUND AND ACCEPTED A 1" IRON
BAR AS WITNESSED BY A MSHD
SURVEY CREW WHILE MAKING A
ROUTE SURVEY IN THE AREA IN
MAY OF 1959. THIS CORNER WAS
ALSO WITNESSED BY DEAN
DELAMETER, RLS, SEE LIBER A,
PAGE 47.

REESTABLISHED W1/4 COR SEC. 29
MIDWAY AND ON LINE BETWEEN
FOUND SECTION CORNERS. AN OLD
FENCE LINE RUNS DUE EAST OF
CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-9	C-10
FD 1" IRON BAR, SET STEEL	SET 1" PIPE W/ALUMN. CAP.
FENCE POST.	6" ASH S19°W 8.73'
TRI. CEDAR 24" N10°W 18.22'	7" ASH S82°E 19.61'
CEGAR 10" S75°W 7.50'	5" ASH N22°W 19.74'
TRI. BIRCH 18" S56°W 14.29'	6" ASH N29°E 41.43'
CEGAR 15" N81°W 9.73'	E-W FENCE NORTH 0.5'
STREAM (COURSE ENE) SOUTH 12'±	

‡ = MDOT WIT.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													



Signed by Carl T. Kiiskila

Date 3-28-97

Surveyor's Michigan License No. 33981