

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Cheboygan (County)	Located In	Corner Code #
1. Public Land Survey	T 34N R 1W	L-3
	T 34N R 1W	M-3
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Section	S T R	
	S T R	
4. Lot No: _____	Recorded Plat: _____	
5. Private Claims: _____		

Register of Deeds Stamp & File Number

I, Carl T. Kiiskila, in a field survey on January 20, 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	19	17	16	15	14	13							
7													
8	18	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

## A. Description of original monument and accessories and/or subsequent restoration:

L3 - ¼ Corner comm. to sec.'s 1&12, T34N,R1W

M3 - Sec. Cor. comm. to sec.'s 1&12, T34N,R1W & sec.'s 6 & 7, T34N, R1E

1850 - GLO - Austin Burt - Set post ¼ sec. corner.  
Sugar 12" S15°E 7 Links  
Sugar 12" N3°W 16 Links

1840 - GLO - John Hodgson/John Mullet - Set post cor. sec.'s 1 & 12  
Beech 8" S31°W 9 Links  
Beech 7" N12°E 18 Links

1951 - Land Corner Record - L.A.p115 - Dean C. DeLamater, P.S.#5778 -  
This corner was established by prop. measurement by For. Div crew, while making a partial resurvey of this township. Set 1" pipe w/4" brass cap.  
18" W.Pine S76°E 217 L  
10" Aspen N21°E 122 L

1951 - Land Corner Record - L.A.p116 - Dean C. DeLamater, P.S.#5778 -  
This corner was established by prop. measurement by For. Div crew, while working in this area. Burned over land, no positive identification. Set 1" pipe w/4" brass cap. 8" H. Maple N70°W 26 L; 7" H. Maple S33°E 108 L  
1996 - Remon L.C.R.C - L.10,p.205 - Brian K. Fullford, P.S.#41099 - Fd. 1" pipe w/4" brass cap. Accepted as a careful and faithful reestablishment of the position of the original corner. 21" Maple N40°E 23.90'; 9" Maple Clump N83°E 21.90'; 5" Maple S66°W 2.05'; 8" & 12" Tw. Maple N71°W 17.03'

## B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

L3 - ¼ Corner comm. to sec.'s 1&12, T34N,R1W

M3 - Sec. Cor. comm. to sec.'s 1&12, T34N,R1W & sec.'s 6 & 7, T34N, R1E

Found DOC monument up 1.5' above ground per Land Cor. Record, L.A.p.115. Corner falls on east face of N-S narrow ridge that GLO called out in random line. Corner is +/-56' east of top of ridge. Accepted found DOC monument as a careful and faithful reestablishment of the position of the original corner. Found no other evidence to dispute the location for the corner.

Found DOC monument up 1.5' above ground per Land Cor. Record, L.A.p.116. Accepted found DOC monument as a careful and faithful reestablishment of the position of the original corner. Found no other evidence to dispute the location for the corner.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L3 - ¼ Corner comm. to sec.'s 1&12, T34N,R1W

M3 - Sec. Cor. comm. to sec.'s 1&12, T34N,R1W & sec.'s 6 & 7, T34N, R1E

Stamped 4" dia. brass cap on 1" galvanized pipe

Stamped 4" dia. brass cap on 1" galvanized pipe

Witnesses:  
N07°E 47.24' to fd. nail on W side 13" W. Pine (dead)  
N68°E 27.51' to set N&T on N side 4" W. Oak  
S34°E 38.31' to set N&T on E side twin 6" & 8" R. Maple  
N52°W 21.02' to set N&T on N side 5" R. Maple  
N16°W 35.25' to set N&T on NE side 6" S. Maple  
Set Blue Carsonite Post 1' North

Witnesses:  
\*N34°E 23.85' to set N&T @ old N&T on S side Triple 12" S. Maple  
\*N83°E 21.52' to fd. nail on S side 9" S. Maple  
S36°E 30.65' to set N&T on E side 4" Beech  
\*S64°W 2.02' to set N&T on S side 8" S. Maple  
Set Blue Carsonite Post 1' North

\* Previous witness of record.

Signed by:

Carl T. Kiiskila

Date:

6-15-10

Surveyor's Michigan License No.:

33981

