

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Cheboygan

(County)

Located In

Corner Code #

1. Public Land Survey

T 34N R 3W C2
T 34N R 3W C1

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Section

S T R
S T R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on April 8, 2008 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-1 G.L.O. C.W. Cathcart 1840, Set post.
Wit: Pine 6" S43°W 10 links
Pine 4" S10°E 5 links

C-2 G.L.O. C.W. Cathcart 1840, Set post.
Wit: Birch 6" N70°W 4 links
Birch 8" S63°E 18 links

1976 Liber 1, Page 201 R. Bischer Fd axle shaft & old hub raised with ½" bar and cap.

Wits: 18" Maple N27°W 62.28'
16" Maple N46°W 86.80'

1976 Liber 1, Page 201 R. Bischer set ½" bar 2640' from the South.

Wits: 17" Maple N15°W 56.96'
P. Pole S76°E 49.52'

1989 Liber 2, Page 41 J. Granger Fd 1/2" bar with cap#15410

Wits: P. Pole N29°E 98.45'
20" Elm S38°W 75.24'
20" Maple S06°E 122.42'
20" Maple N20°W 61.71'

1989 Liber 2, Page 41 J. Granger Fd 1/2" bar with cap#15410

Wits: 14" Maple N19°W 31.95'
5" Maple N00°W 28.48'
P. Pole N82°E 49.48'
30" Maple S30°W 6.37'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

C-1 Found ½" bar fitting R. Bischer's survey and J. Granger's witnesses.

C-2 Found ½" bar fitting R. Bischer's survey and J. Granger's witnesses.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-1 Added P.S. cap #33981 to found ½" bar

Wit: Nail and tag S side of P. Pole S69°W 7.43'
Nail and tag SW side of 7" Elm S31°E 61.21'
Nail and tag NE side of P. Pole N41°W 122.67'
Co. Monument N84°W 9.06'

C-2 Drove 1" X 36" Pipe with P.S. cap #33981 over found ½" bar

Wit: Nail and shiner S side of P. Pole N82°E 49.34'
Nail and tag N side of Maple N54°W 15.48'
Nail and tag SW side of 18" Maple N20°W 31.84'
Nail and tag S side of 9" R. Pine S60°E 81.88'

Signed by:

Carl T. Kiiskila

Surveyor's Michigan License No.:

33981

Date:

8-18-08

