

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. 34 N. R. 3 W.		E-9 E-10
2. PROPERTY CONTROLLING IN SECTION 28, T. 34 N. R. 3 W.		5; 6
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on September 11, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- E-9 Found 3" wagon axle at road intersection, as previously located in 1961 survey of this area. Fits adjacent occupation.
- E-10 Set corner by single proportionate measurement, midpoint on line, between section corners. Falls in line with old fence lines E and W.
- 5 Set corner by standard survey procedure for the subdivision of sections.
- 6 Set corner by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-9	E-10	5
Fd. 3" Axle Shaft	Set DNR Monument	Set 5/8x40" iron bar w/RLS Cap
*13" Dead Elm N21°E 60.75	6" S. Pine N49°W 19.2	4" Maple S25°W 20.50
8" Maple Clstr. S54°W 66.3	7" Maple S35°W 36.5	12" Maple N37°W 14.7
*1961 NBT by DNR		
	6	
	Set 5/8x40" Iron Bar w/RLS Cap	
	10" Basswood S18°W 13.7	
	8" Basswood N58°E 5.8	

SIGNED BY Kenneth J. Ostling

DATE 11-1-78

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ CHIEF OF SURVEY PARTY

DATE _____

APPROVED AND SIGNED BY _____ MICHIGAN REGISTERED LAND SURVEYOR

DATE _____

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

CHEBOYGAN COUNTY