

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY—	T. 34 N. R. 3 W.	G-10; G-11; H-11
2. PROPERTY CONTROLLING IN SECTION—	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION—	T. N. S. R. E. W.	
4. LOT NO.—, RECORDED PLAT—		
5. PRIVATE CLAIMS—		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 27, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 10 Recovered DNR monument as established by proportionate measurement in 1961 survey in this area.
- 11 Found 3/4" pipe in place at same location as was noted in 1961 survey in this area.
- 11 Found 1" iron bar at corner at same location as noted in 1961 survey in this area. Falls in center of E-W county road.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-10	G-11	H-11
DNR monument in place	Left 3/4" Pipe in place	Set 3/4" pipe on top of 1" bar
Elm stp. N10°E 24.45	10" W. Pine N25°E 68.4	8" Maple N34°E 43.0
11" W. Pine N20°E 42.1	SW corner con. foundation	8" Maple S37°E 28.45
18" R. Pine S87°E 24.2	of house N52°E 46.95	Cedar Post North 22'

SIGNED BY Kenneth J. Ostling DATE 12

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068


FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR



(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

MENTOR TOWNSHIP
CHEBOYGAN COUNTY