

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Cheboygan
(County)

Located In

Corner Code #

1. Public Land Survey T 35N R 1E H-4
T 35N R 1E H-5

2. Property Controlling in Section S T R
S T R

3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on December 6, 2011 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|---|----|---|----|---|----|---|----|---|----|---|---|
| 1 | | | | | | | | | | | | | |
| 2 | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | | |
| 3 | | | | | | | | | | | | | |
| 4 | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | | |
| 5 | | | | | | | | | | | | | |
| 6 | 18 | | 17 | | 16 | | 15 | | 14 | | 13 | | |
| 7 | | | | | | | | | | | | | |
| 8 | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | | |
| 9 | | | | | | | | | | | | | |
| 10 | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | | |
| 11 | | | | | | | | | | | | | |
| 12 | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | | |
| 13 | | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:

H-4 – Center ¼ Corner section 10, T35N, R01E

H-5 – ¼ Corner common to sections 10 & 15, T35N, R01E

1949 – Cheboygan Co. Land Corner Record – L.a, p.267 – Orlando Doyle, RLS #7319 – Concrete monument set. 7" Oak N86°15'W 16.95'; 7" Oak N27°30'E 28.22'

1984 – L.C.R.C. – L.1, p.318 – Orlando Doyle, RLS #7319 – Same info as above.

1989 – L.C.R.C. – L.2, p.94 – James H. Granger, P.S. # 16041 – Fd. conc. mon. 12" R. Oak N86°W 16.98'; 12" R. Oak N28°E 28.47'; 14" R. Pine S19°E 17.29'; 8" R. Pine N5°W 54.36'

1840 – GLO – Brevort- Set qr. section post.
Sp. Pine 7 S45°W 40
Y. Pine 20 N28°E 72

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

H-4 – Center ¼ Corner section 10, T35N, R01E

H-5 – ¼ Corner common to sections 10 & 15, T35N, R01E

Found and accepted 4" dia. x 4' long concrete monument per 1949 Land Corner Record L.a, p.267 as the best available evidence for the position of the corner. Shortened conc. mon. by 6" to set lower in 2-track road. Placed ½" plastic P.S. cap #33981 on monument. Corner falls 2' East of C/L N-S 2-track trail road. Also found ¾" pipe of no record N30°W 3.08'. Found no other evidence to dispute the location for the corner.

Found and accepted 2" dia. pipe in trail road intersection 6" below grade as the best available evidence for the position of the original corner. Drove 60D spike in center of pipe. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-4 – Center ¼ Corner section 10, T35N, R01E

H-5 – ¼ Corner common to sections 10 & 15, T35N, R01E

4" diameter x 3.5' long conc. mon. w/ ½" plastic cap #33981.

2" diameter iron pipe w/60D spike in center of pipe.

Wit: *N25°E 28.32' to set N&T on W side 14" Oak
*S22°E 17.25' to set N&T on W side 17" R. Pine
N84°W 36.50' to set N&T on N side 5" W. Pine
N30°W 3.08' to fd. ¾" pipe
*N10°W 54.49' to set N&T on W side 12" R. Pine
Set Blue Carsonite Post w/ location tag 10' East
* Witness of previous record.

Wit: *N49°E 30.39' to set N&T on NW side 14" R. Pine
*S21°E 39.49' to set N&T on E side 14" R. Pine
S41°W 34.93' to set N&T on NW side 9" J. Pine
N41°W 45.86' to set N&T on NE side 12" Oak

* Scribed 'XBT' on bottom blaze.

Signed by:

Carl T. Kiiskila

Date:

5-1-12

Surveyor's Michigan License No.:

33981

