

# SURVEY & REMONUMENTATION

FEB 26 1998

## SECTION

### CHEBOYGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
Cheboygan  
(County)

Located In:

Corner Code #

1. Public Land Survey

T36NR 3W

K-11

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property In Sec.

S T R

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Brian K. Fullford, in a field survey on Sept. 17, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

RECEIVED FOR RECORD 12-18-97  
at 11:14 O'Clock A M

*Joanne Spray*

CLERK/REGISTER  
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. 1947 Orlando Doyle  
1855 Harvey Mellen #7319  
Re-establish old Set Conc. Mon.  
corner E. Cor. on front of Stone  
10" W. Pine S 60° E 6 Cottage N 50° E 74.85'  
lks SW Cor. Stone Cottage  
12" Spruce S 21° W N 27° E 77.70'  
12 lks

1978 Assessor's Plat  
of Sunset  
Beach George Young  
#10710  
Concrete Monument

1992 Norm Quaine #33984  
1/2" Rod & cap #15410  
Conc. Mon. S 51° E 84.67'  
P. Pole S 41° W 41.60'  
SE Cor. Stone Cottage  
N 50° E 74.85'  
NW Cor. Stone Cottage  
N 27° E 77.70'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" bar and cap #15410 and 4 witnesses.

LIBER 011 PAGE 18



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-11 Placed 5/8" rebar with remonumentation cap over top of 1/2" bar and cap, and is accepted as a careful and faithful perpetuation of the original corner.

N.W. Corner Stone Cottage N 31° E 77.55'  
S.E. Corner Stone Cottage N 56° E 74.65'  
Concrete Monument S 44° E 84.67'  
P. Pole S 45° W 41.60'

W/Tag 15410

Signed by

*Brian K. Fullford*

Surveyor's Michigan License No.

41099

Date

11/21/97

