

MAR 22 1999

1998

CHEBOYGAN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in  
Cheboygan

(County)

Located In:

Corner Code #

1. Public Land Survey

T 36N R 3W

C-1

T 37N R 3W

C-13

T R

T R

2. Property Controlling  
in Section

S

T R

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

S

T R

RECEIVED FOR RECORD 1-8-99  
at 8:58 O'Clock A M

*Joanne Spray*

CLERK/REGISTER  
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Brian K. Fullford, in a field survey on June, 19 98, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

NOTE: THIS CORNER IS ALSO DESIGNATED C-13, T37N-R3W.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

1840 John Mullett  
Original Survey  
Set section post  
10" Beech N 13° W 13 lks  
(8.58')  
12" Beech N 55° E 44 lks  
(29.04')

Sept. 1976  
Herbert Fluharty #18223  
Set 5/8" X 18" Re-rod w/cap  
equidistant on line between N  
1/4 Cor. Sec. 6 & NE Cor. Sec. 5,  
Support pole S 23° E 54.00'  
T.P. S 52° W 60.03'

P.P. N 28° E 51.24'  
8' ± N of E-W Road, 15' ± E of  
road to N, 8' ± W of centerline  
Woods Rd to South

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fnd 5/8" re-rod w/unreadable Cap  
Under Asphalt Road  
8' +/- North Centerline E-W Road  
15' +/- East Centerline Road to North  
8' +/- West Centerline Wood Road to South

P. Pole w/Nail Cut off at ground S 23° E 53.80'  
T. Pole 4' High S 52° W 59.95' w/nail  
P. Pole #1590 N 35° E 54.90'  
Guy Pole S 25° E 56.79'  
8" Hemlock S 7° W 81.73'

SEP 24 1998

*James H. Kruger*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-1 Placed remonumentation cap on 5/8" rebar in monument box, and position is accepted as a careful and faithful perpetuation of the original corner.

P. Pole Cut off at grade S 23° E 53.80' w/nail  
T. Pole 4' High S 52° W 59.95' w/nail  
P. Pole #1590 N 35° E 54.90' Set tag 41099  
Guy Pole S 25° E 56.79' Set tag 41099  
8" Hemlock S 7° W 81.73' Set tag 41099

NOTE: THIS CORNER IS ALSO DESIGNATED CODE C-13 IN T37N-R3W.

Signed by *B. K. Fullford*  
Surveyor's Michigan License No. 41099

Date 11/23/98

