SURVEY & REMONUMENTATION

MAR 2 1 1997 () DELTA COUNTY CODE NO.

Approved by Delta County Land Survey Remonumentation Peer Group Under Act 345 Of

MOISSHALL		Ρ.Ε
COMMISSION	LAND CORNER RECORDATION CERTIFIC	ATE

			uirement of Act 74, Mich. P.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		l
	corners in DELTA					
	(County)	Located In:	Corner Code #		Jan 21	991
	.	_ 20 v _ 22 **	(Mher)	Record	· · · · · · · · · · · · · · · · · · ·	D A
1. [Public Land Survey	т <u>38 N</u> R <u>23 W</u> т <u>38N</u> R <u>23 W</u>		¥	3:00 68604	TNC
	T R	-	1.99	<u> 8 Page </u>	٥3	
		TR			giletter &	. Zz.
2. 1	Property Controlling	S T R		Celta Co	unty, Mil Sog. of Creds	
i	n Section	S T A				
	Miscellaneous	S T R		Register of De	eds Stamp & File	Numbe
ì	Property in Sec.	S R	L			
I . 1	_ot No.	Recorded Plat				
	Private Claims			A B	CDEFGH	$\dot{\uparrow}$ $\dot{\uparrow}$ $\dot{\uparrow}$
	C-11/12 [MC C	OR @ LAKE MICH.] CD-11 [MC	COR AT LAKE MICH.]	2 6	- 5 4 3 -	
				3		1 1-1
	M.P. DAVIS		MAY	4 7	- 8910	+-11-+
lo he			MAY , 19 <u>96</u> P.A. of 1970, the corner points mention	oned 5		1-1-1
n lin	es 1 and 2 above were	in conformance with regulations	and rules therefore as required in	n the " 18	-17-16-15-	
			partment of the Interior, Bureau of I orner points mentioned in lines 3, 4 a			+
			rd of Land Surveyors or by a Decree	enfa	-20-2122-	23
Cour	t of Law; established,		re-monumented, recovered, found	dias *	- - - - - - - - - -	1 1
•	essed below:			10 30	29 28 27	26
TOP			and range, may be recorded	11	•	1
	on this certificate	•		12 -31	32 33 34	35-
C/	D-11 [MC COR @ LAKE MI	CH.] WOOD POST - A.MERRYWEAT	ER "B" OF PLATS PG. 50-REFLACED HER,D.S 1847 (TAMARACK 08'-N	(54°W-32 LINKS) (TAM	ARACK 07"-S72°W-38	
C/	D-11 [MC COR @ LAKE MI M.S.McNABB-1922-W	CH.] WOOD POST - A.MERRYWEAT OD STAKE IN PLACE-NO NEW WIT		454°W-32 LINKS) (TAM MINED IN HIS RECORDS	ARACK 07"-S72°W-38	
3. 1 C-	D-11 [MC COR @ LAKE MI M.S.McNABB-1922-WC M.D.O.TR/W PLANS Description of corner 11/12 (REF. MON.) FOUN FOR THE MEANDER 4" SQUARE CONC 1927 SURVEY OF 50 BY MEASUREME	CH.] WOOD POST - A.MERRYWEAT OD STAKE IN PLACE-NO NEW WIT FOR STATE HWY. PROJECT #21- evidence found and/or method in Place, on N. SIDE OF FE CORNER AS MEASURED SOUTH FR MONUMENT. ID THE EXISTING MOSUPERVISOR'S PLAT NO. 1 FORD INTS TO ADJOINING PLAT MONUME ID FROM M.D.O.T. SURVEY TIES	HER,D.S 1847 (TAMARACK 08'-N'S NOTED OR OTHER REMARKS CONTA 16B SHOW CORNER IN PLACE-NO WIT od applied in restoring or reesta NCE POST & 60.0 FEET SOUTH OF T OM THE NW CORNER OF SEC 32, A 5 NUMENT AS BEING THE SAME AS SET RIVER TWP. & REC'D IN LIBER "B NTS.	454°W-32 LINXS) (TAM AINED IN HIS RECORDS I'S GIVEN Abhishing corner: PHE "GLO" DISTANCE 1/8" I.P. SET IN A BY MCNABB IN HIS I' OF PLATS ON PAGE	ARACK 07"-S72"#-38	MIC. I. P. AVIS SURVEYOR NO.
3. 1 C-	D-11 [MC COR @ LAKE MY M.S.McNABB-1922-WC M.D.O.TR/W PLANS Description of corner of 11/12 (REF. MON.) FOUN FOR THE MEANDER 4" SQUARE CONC 1927 SURVEY OF 50 BY MEASUREME D-11 FOUND IN PLACE & EXISTING MONUMENT	CH.] WOOD POST - A.MERRYWEAT OD STAKE IN PLACE-NO NEW WIT FOR STATE HWY, PROJECT #21- evidence found and/or method IN PLACE, ON N. SIDE OF FE CORNER AS MEASURED SOUTH FR MONUMENT, ID THE EXISTING MO SUPERVISOR'S PLAT NO. 1 FORD INTS TO ADJOINING PLAT MONUME ID FROM M.D.O.T. SURVEY TIES CHECKS WELL WITH "GLO" DIST	HER,D.S 1847 (TAMARACK 08'-N'S NOTED OR OTHER REMARKS CONTA 16B SHOW CORNER IN PLACE-NO WIT od applied in restoring or reesta NCE POST & 60.0 FEET SOUTH OF T OM THE NW CORNER OF SEC 32, A 5 NUMENT AS BEING THE SAME AS SET RIVER TWP. & REC'D IN LIBER "B	454°W-32 LINKS) (TAM AINED IN HIS RECORDS I'S GIVEN Abhishing corner: PHE "GLO" DISTANCE 5/8" I.P. SET IN A BY MCNABB IN HIS I' OF PLATS ON PAGE	ARACK 07"-S72"W-38	MIC. P. AVIS SURVEYOR
C/I	D-11 [MC COR @ LAKE MI M.S. McNABB-1922-WC M.D.O.TR/W PLANS Description of corner of 11/12 (REF. MON.) FOUN FOR THE MEANDER 4" SQUARE CONC 1927 SURVEY OF 50 BY MEASUREME D-11 FOUND IN PLACE & EXISTING MONUMENT RECORDS. ACCEPTED ORIGINAL CORNER. Description of monum- 11/12 (REF. MON.) DID CEDAR 13" C N06°E	CH.] WOOD POST - A.MERRYWEAT OD STAKE IN PLACE-NO NEW WIT FOR STATE HWY, PROJECT #21- Evidence found and/or method IN PLACE, ON N. SIDE OF FE CORNER AS MEASURED SOUTH FR MONUMENT. ID THE EXISTING MO SUPERVISOR'S PLAT NO. 1 FORD INTS TO ADJOINING PLAT MONUME ID FROM M.D.O.T. SURVEY TIES CHECKS WELL WITH "GLO" DIST. AS BEING THE BEST AVAILABLE	HER,D.S 1847 (TAMARACK 08'-N'S NOTED OR OTHER REMARKS CONTA 16B SHOW CORNER IN PLACE-NO WIT od applied in restoring or reesta NCE POST & 60.0 FEET SOUTH OF T OM THE NW CORNER OF SEC 32, A 5 NUMENT AS BEING THE SAME AS SET RIVER TWP. & REC'D IN LIBER "B NTS. TO C/L OF STATE HWY. M-35 A 11 ANCE EAST OF NW CORNER OF SEC 3 EVIDENCE AS TO THE LOCATION OF	454°W-32 LINKS) (TAM AINED IN HIS RECORDS I'S GIVEN Abhishing corner: THE "GLO" DISTANCE 16/8" I.P. SET IN A THE BY MCNABB IN HIS TOF PLATS ON PAGE 1.72" GALV IRON PIPE. THE POSITION OF THE Cating the position of NOTE: BT'S ARE LOCAL	ARACK 07"-S72"W-38 LAND of the corner: ATED IN RESIDENTIAL ALLS ONLY, NO SCRIP	MIC. I. P. AVIS SURVEYOR 6926 LAND
C/I	D-11 [MC COR @ LAKE MY M.S.McNABB-1922-WC M.D.O.TR/W PLANS Description of corner of 11/12 (REF. MON.) FOUN FOR THE MEANDER 4" SQUARE CONC 1927 SURVEY OF 50 BY MEASUREME D-11 FOUND IN PLACE & EXISTING MONUMENT RECORDS. ACCEPTED ORIGINAL CORNER. Description of monument 11/12 (REF. MON.) DID CEDAR 13" C N06°E 43.75' D-11 PLACED OVER EXIST CEDAR 09" C N80°E	CH.] WOOD POST - A.MERRYWEAT OD STAKE IN PLACE-NO NEW WIT FOR STATE HWY. PROJECT #21- EVIDENCE FOUND AND/OF METHOD OF IN PLACE, ON N. SIDE OF FE CORNER AS MEASURED SOUTH FR MONUMENT. ID THE EXISTING MO SUPERVISOR'S PLAT NO. 1 FORD NTS TO ADJOINING PLAT MONUME ID FROM M.D.O.T. SURVEY TIES CHECKS WELL WITH "GLO" DIST. AS BEING THE BEST AVAILABLE ENT FOR COMMETTED AND AND AND AND AND AND AND AND AND AN	HER, D.S 1847 (TAMARACK 08'-N 'S NOTED OR OTEER REMARKS CONTA 16B SHOW CORNER IN PLACE-NO WIT od applied in restoring or reesta NCE POST & 60.0 FEET SOUTH OF T OM THE NW CORNER OF SEC 32, A 5 NUMENT AS BEING THE SAME AS SET RIVER TWP. & REC'D IN LIBER "B NTS. TO C/L OF STATE HWY. M-35 A 11 ANCE EAST OF NW CORNER OF SEC 3 EVIDENCE AS TO THE LOCATION OF ES ESTABLISHED TO THE LOCATION OF ANCE MICHIGAN SHORE LINE SOUTH 180' M/L UM MONUMENT WITH THE CAP STAMPER HT SIGN POST LAKE MICHIGAN LAKE MICHIGAN LAKE MICHIGAN THE STAMPER THE SIGN POST LAKE MICHIGAN THE STAMPER THE STAMPE	ACT OF PLATS ON PIPE. CATING THE POSITION OF THE POSITION OF THE POSITION OF THE PLACED REF NAME OF THE PLACED REF NAME OF THE POSITION OF THE PLACED REF NAME OF THE POSITION OF THE PLACED REF NAME OF THE POSITION OF THE POSITION OF THE POSITION OF THE PLACED REF NAME OF THE PLACED REF NAME OF THE PLACED REF NAME OF THE POSITION OF THE PLACED REF NAME OF THE POSITION OF THE PLACED REF NAME OF THE PLACED REF NAME OF THE POSITION OF THE PLACED REF NAME OF THE PLACED REF NAME OF THE PLACED REF NAME OF THE PLACED REPORTS OF THE PLACED REPOR	ARACK 07"-S72"W-38 Cof the corner: ATED IN RESIDENTIAL ALLS ONLY, NO SCRIP	MIC. I. P. AVIS SURVEYOR 6926 LAND

______ Date ____