REMONUMENTATION

SEP 1 3 1994

Approved By Delta County Land Survey Remonumentation

Peer Group Under Act 345 Of _, 199<u>4</u> A. Of 1990 On 1

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Octoin Chairman

Fo	r corners in DELTA	Located In:	Corner Code ##							V		
	(County)	Located III.	/									
1.	Public Land Survey	T 39 N R 24 W T R T R	<u>I-7 & (I-8)</u>	Records	d	UN .	********	-	8		- 20	
		T R		-	-					E E		
2.	Property Controlling	\$ T R		gile	Steel .	ج.	Z		_ Rog.	of Deac	15.	
	in Section	S T R	 ,	Data C	ounty.	ivictie	gan					
3.	Miscellaneous	S T R		Regi	ster c	f De	eds S	tamp	& File	Num	ber	
	Property in Sec.	S T R										
	,											
4.	Lot No , R	ecorded Plat			A	в с	D	E F	GН	I J	К	L M
5.	Private Claims	AP C 221 1-9 [M1// CAP C 22]			2							1
	1-1 Int C	ON 5.25) 1-0 [41) 4 CON 5.25]			3	Ĭ	_ ;	Ī	Τĭ			-
					·	T T	_					
	M.P. DAVIS		MAY 19 94	•	4	7	- 8 	 		 	_	-12-
l, _		in a field survey onuirements of P.A. 74, Michigan P.A.		oned	5 —		+		1-1-		\top	†
in	lines 1 and 2 above were in	conformance with regulations an	nd rules therefore as required in	n the	6	18	17	16-	15-	14	\neg	-13-
cui	rrent manual of survey instru	ctions of the United States Depar	tment of the Interior, Bureau of I	Land	7		+-	- 	+++	+	+	┿┥
Ма	nagement or by a decree of a	Court of Law and/or that the corne	er points mentioned in lines 3, 4 a	and 5	в	المارة	-20	21-	22-	23	+	-24
ab	ove were in conformance with	h the rules of the Michigan Board o e-established,monumented,re-r	or Land Surveyors or by a Decree monumented, recovered, foun	eora das ·	9	-			+	++		
	pressed below:	e-ostabilotios, monamontos, ro	monanted, resoluted, real.		10;	30	-29	28	27-	26-	-	-25-
NC	TF: Not more than 4 co	orners, all in the same town a	nd range, may be recorded		11				1-1-	\downarrow	4	1
	on this certificate.				12	1		33	34-	35		-36
					13	Ï	Ī	lï				
	I-7 [NW COR S.23] GEORGE D.A.BROTHERTON - 1896 M.S.McNABB - 1913 - S I-8 [W1/4 COR S.23] GEORG D.A.BROTHERTON - 1896 M.S.McNABB - 1913 - I M.S.McNABB - 1919 - I	ADAIR, D.S 1852 - WOOD POST - IDENTIFIED CORNER POSITION TAKE IN HWY - FENCE POST N27°E - ADAIR, D.S 1852 - WOOD POST - IDENTIFIED FROM ORIGINALS - DENTIFIED FROM RECORDS & NOTED DENTIFIED FROM PREVIOUS SURVEY DENTIFIED FROM PREVIOUS SURVEY	(W.PINE 18"-N62°E-44 LINKS) FROM ORIGINALS & NOTED NEW FE-23' T (HEMLOCK 14"-N68°E-17 LINKS NO NEW WIT'S NOTED TO NEW BT (ELM-4"-N10°E-7') T -PINE STUMP-N75°W-28.0'	(TAMARACK ET (HEMLOCI	K 10*- K 12"-	N74°3 S57°W	0'E-5	14.7')				

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 - I-7 [NW COR S.23] COMPASS & CHAIN WEST FROM THE N1/4 COR SEC 23 TO THE APPROX CORNER POSITION AND POSITIONED A TEMPORARY COR FROM THE GLO TERRAIN CALLS TO THE SWP EDGE 1 CHAIN NORTH AND 2 CHAINS EAST. FROM THIS POINT A SEARCH FOR THE GLO BT'S WAS MADE, AT THE APPROX GLO DISTANCE AND BEARING FROM THE TEMPORARY COR A LARGE PINE STUMP WAS RECOVERED. THE STUMP IS IN SUCH A STATE OF DECAY AS NOT TO PERMIT THE IDENTIFICATION OF ANY IRON MARKS OR THE MEASURING NOTCH. BECAUSE OF THE CORRELATION OF THE TERRAIN CALLS & THE PINE STUMP I HAVE ACCEPTED THE PINE STUMP AS BEING THAT OF THE GLO & HAVE RESET THE COR S62'W-44 LINKS FROM THE PINE STUMP AS PER RECORD.
 - I-8 [W1/4 COR S.23] FOUND IN PLACE A 1" IRON PIPE. IDENTIFIED COR POSITION BY GLO CALLS SOUTH TO THE 10 MILE CREEK & THE REMAINS OF AN OLD FARM FENCE N & S. FROM THE 1.P. THE REMAINS OF AN ELM STUMP BEARS \$22'W-92.6' & A PINE STUMP (MEASURING NOTCH PLAIN) BEARS N75'W-28'. ACCEPTED EXISTING MONUMENT AS BEING A CAREFUL & FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.



C.	Description of me	onument for corner	and accessories	established t	to perpetuate	locating the	position (of the corner:
----	-------------------	--------------------	-----------------	---------------	---------------	--------------	------------	----------------

I-7 SET A BERNTSEN	A1NB30 ALUMN	MONUMENT WITH THE CA	P STAMPED TO ID	THE CORNER POSITION.
BALSAM 8"	SPRUCE 10*	SPRUCE 9*	SPRUCE 7*	SURVEY MONUMENT SIGN POST
N7°W	N61°E	S12°E	s86°W	\$45°E
30.33'	25.801	36.29'	22.541	2.25' (TO FACE)

ERNT A REPORTSEN ALUBSO ALUMN MONUMENT WITH THE CAP STAMPED TO ID THE CORNER POSITION.

I-8	SET OVER EXISTING	MONUMENT A	BERNTSEN AINBJU.	ALUMN MUNUMENT WITH	A THE CAP ST	ŧ
	W.BIRCH 13" Y	BIRCH 14"	SPRUCE 9*	SURVEY MONUMENT	SIGN POST	
	N46°W	\$35°W	S80°W	South		
	33.601	31.001	76.40'	2.20' (40	FACE)	

NOTE: BEARINGS TO REFERENCE OBJECTS ARE MAGNET	IC & DIS	TANCES ARE TO A	NAIL W/A	REFERENCE TAG IN THE OBJECT, UNLESS OTHERWISE NOTED.
Signed by Milassii			Date	6/1/94
Surveyor's Michigan License No. 16926				FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
	LIBER .	. 8 PAGE	20	REVISED MAY 14, 1975 REVISED JAN., 1983