OCT 2 6 1995

Approved by Della County Land Survey Remonumentation Peer Group Under Act 345 Of Of 1990 On June 6 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

For	corners in	Fili	ng Requirem	nent of Act 74,	Mich. P.A.		Kg Chair	nan		
	DELTA (County)	Located I	n:	©Corner Code =	#					
1.	Public Land Survey		R 19 W	E-7/8 & K		Recorded .	JUN 13	1995		
		Υ	R R			# 9:00 _{0'c}	lockA-M-i	Liber <u>8</u>	Páge	57
	Property Controlling	S T	R			Walls	u c. Z	Z	Reg. of E	Deeds.
	in Section Miscellaneous	S T S T					ty, Michigan of Deeds !		Eila N.,	
	Property in Sec.	s T	R					Jenip &	- HE NO	
		, Recorded Plat				A	всо	E F G	ні.	j K L
5.	Privatę Claims	E-7/8 [S.M.C.]	K-3 [NW CC	OR SEC 12]			65	4	-3-	2 1 -
-						3		 	-	
1,	M.P. DAVIS	, in a field survey or	,DECEMBER	?	19 _ 94	. 5	- [†] 8		-10	11-12
in lin Curre Mana abov Cour	ereby certify that under rites 1 and 2 above were ent manual of survey insagement or by a decree of were in conformance.	requirements of P.A. 74, Note in conformance with restructions of the United State of a Court of Law and/or the Wich the rules of the Mich pre-established, monuting the monuting of the Mich pre-established, monuting the monuting of the Mich pre-established, monuting the monuting of the Mich pre-established.	Michigan P.A. of gulations and re States Departmentat the corner policy of L. Grant Board of L. Migan Board of L.	1970, the corner poi rules therefore as r ent of the Interior, E oints mentioned in and Surveyors or b	equired in the sureau of Land lines 3, 4 and 5 y a Decree of a	e 7	-1317 -1320 -3029	21 28	22	23 24
NOT	E: Not more than 4 on this certificat	corners, all in the sa	me town and	range, may be re	corded	11	-31	32	+ + -	35—36
•		ai monument and acce				13	3 32	33	1	35 36
. , , , , , , , , , , , , , , , , , , ,	M.S.McNABB-1920-FO M.DAVIS-1973-FOUND SET I.P. W/A SURVE "PK" NAIL IN SOUTE	SEC 21] NOT ESTABLISH L.MERRYWEATHER, D.S DUND + ON STONE - CEDA IN PLACE IRON STAKE IY CAP OVER EXISTING M I ROOT OF SPRUCE 291-N evidence found and/ SEC. 21] ESTABLISHED	1848 - WOOD PO R 4*-548°E-55' & STONE WITH CONUMENT & NOTE 11°W-114.94' &	OST (BIRCH 09"-S5: 4 + ON STONE N3: CHISELED CROSS, NO DD NEW BT'S (CROSS) REC'D ON 2/25/7:	0°W-111.2' DEVIDENCE OF SEIN STONE-NO IN LIBER 1 OF FEESTABLES	F McNABB'S 80°W-112.0' OF LCR'S O	BT'S) (CEDAR 8 N PAGE 409		5.25')	
	STURGEON RIVER B	ED. FOUND IN PLACE MONUME MONUMENT AS THE BEST	NTS AS DESCRIE	BED ABOVE & BT'S	AS PREVIOUSL'	Y RECORDED.	A CONTRACTOR AND A CONT	DA LAND SI	Ю.	C P TO TO THE PARTY OF THE PART
	,	•						~ ~ ~ ~	A44 20 3	
	-7/8 SET BERNTSEN A1	nent for corner and ac NB30 ALUMN MON. W/A 3 SURVEY MONUMENT SIGN SOUTH 1.82' (TO FACE	1/4" CAP STAMP POST NO		ER POSITION. S AVAILABLE	. CORNER PO		comer:		
X	SPRUCE 6' CE N72°E S	42°E N8	18" REBAR W/A LE IN STONE 3°W 210'	SURVEY MONUM WES	INT SIGN POST		R POSITION			
			•							
N	OTE: BEARINGS TO REFE	RENCE OBJECTS ARE MAGI	VETIC-DISTANCE				NCE TAG, UI	ILESS OTHE	KRWISE N	OTED.
Sign	ed by	AUI			ate <i>4//</i> _	3/95				

Surveyor's Michigan License No. 16926